


Mole cilindriche TOUGH

La forma cilindrica ZY è ottimale per la lavorazione di fori, raggiature e profili.



D x T [mm]	Granulometria							Corrisp. alla forma USA	N. giri consigliato	N. giri max.		Denominazione
	24	30	46	60	80	100	320					
EAN 4007220												

Diam. gambo 3 x 30 mm [S_d x L₂]


1 x 5	-	-	-	-	-	-	898383	-	104.200	104.200	10	ZY 0105 3 AWCO ... J5V TOUGH
1,5 x 8	-	-	-	-	-	-	898390	-	104.700	104.700	10	ZY 1,508 3 AWCO ... J5V TOUGH
1,7 x 8	-	-	-	-	-	-	898406	-	112.300	112.300	10	ZY 1,708 3 AWCO ... J5V TOUGH
2 x 5	-	-	-	-	898413	898420	-	W 141	150.000	201.800	10	ZY 0205 3 AWCO ... J5V TOUGH
3 x 6	-	-	-	898437	802106	802120	-	W 144	150.000	206.100	10	ZY 0306 3 AWCO ... J5V TOUGH
4 x 8	-	-	-	898444	802137	802144	-	-	150.000	175.100	10	ZY 0408 3 AWCO ... J5V TOUGH
5 x 10	-	-	-	898451	802151	802168	-	W 153	130.700	130.700	10	ZY 0510 3 AWCO ... J5V TOUGH
6 x 13	-	-	898468	802175	802182	802199	-	W 163	93.600	93.600	10	ZY 0613 3 AWCO ... J5V TOUGH
8 x 10	-	-	947852	-	-	-	-	W 169	87.600	87.600	10	ZY 0810 3 AWCO ... J5V TOUGH
8 x 16	-	-	898475	898499	898505	-	-	-	61.000	61.000	10	ZY 0816 3 AWCO ... J5V TOUGH
10 x 13	-	-	-	947869	-	-	-	W 176	58.400	58.400	10	ZY 1013 3 AWCO ... J5V TOUGH
13 x 3	-	-	-	898574	-	-	-	W 182	65.000	73.400	10	ZY 1303 3 AWCO ... J5V TOUGH
20 x 6	-	-	898581	898598	-	-	-	W 201	45.000	47.700	10	ZY 2006 3 AWCO ... J5V TOUGH

Diam. gambo 6 x 40 mm [S_d x L₂]

5 x 10	-	-	-	-	947876	-	W 153	150.000	157.800	10	ZY 0510 6 AWCO ... J5V TOUGH	
8 x 16	-	-	802205	-	802212	-	-	-	100.000	119.300	10	ZY 0816 6 AWCO ... J5V TOUGH
10 x 13	-	-	802229	-	802274	-	-	W 176	85.000	95.400	10	ZY 1013 6 AWCO ... J5V TOUGH
10 x 20	-	-	898512	-	898550	-	-	-	85.000	95.400	10	ZY 1020 6 AWCO ... J5V TOUGH
13 x 25	-	-	802304	-	802311	-	-	W 187	65.000	66.000	10	ZY 1325 6 AWCO ... J5V TOUGH
16 x 20	-	947883	802328	802335	-	-	W 195	55.000	59.600	10	ZY 1620 6 AWCO ... J5V TOUGH	
16 x 32	-	947890	802342	802366	-	-	-	-	51.200	51.200	10	ZY 1632 6 AWCO ... J5V TOUGH
20 x 25	-	947906	802373	802397	-	-	W 205	45.000	47.700	10	ZY 2025 6 AWCO ... J5V TOUGH	
20 x 40	-	947913	898604	898628	-	-	W 207	32.400	32.400	10	ZY 2040 6 AWCO ... J5V TOUGH	
25 x 25	-	947920	-	-	-	-	W 220	35.000	38.100	10	ZY 2525 6 AWCO ... J5V TOUGH	
32 x 16	-	-	947937	-	-	-	-	-	27.000	29.800	5	ZY 3216 6 AWCO ... J5V TOUGH
32 x 32	947944	-	802427	-	-	-	W 230	25.700	25.700	5	ZY 3232 6 AWCO ... J5V TOUGH	
40 x 10	-	-	898635	898642	-	-	W 236	22.000	23.800	5	ZY 4010 6 AWCO ... J5V TOUGH	
40 x 20	-	-	802434	-	-	-	-	-	22.000	23.800	5	ZY 4020 6 AWCO ... J5V TOUGH

Mole sferiche TOUGH

La forma a sfera KU viene spesso impiegata per molare profili e spigoli situati posteriormente, difficili da raggiungere.



D [mm]	Granulometria				N. giri consigliato	N. giri max.		Denominazione
	46	60	80	100				
EAN 4007220								

Diam. gambo 3 x 30 mm [S_d x L₂]

3	-	898659	898666	-	150.000	300.200	10	KU 03 3 AWCO ... J5V TOUGH
6	-	898673	802465	802472	140.000	159.100	10	KU 06 3 AWCO ... J5V TOUGH
8	898680	-	802489	802519	100.000	116.200	10	KU 08 3 AWCO ... J5V TOUGH

Diam. gambo 6 x 40 mm [S_d x L₂]

13	802533	802557	802595	-	65.000	73.400	10	KU 13 6 AWCO ... J5V TOUGH
----	--------	--------	--------	---	--------	--------	----	----------------------------