



Doglegs on several levels.



Supply format

REMS Python Set. Oil-hydraulic pipe bender for dimensionally accurate bending of pipes up to 90°. Steel pipes EN 10255 Ø ¾–2", multilayer composite tubes Ø 32–75 mm. Drive unit with back former supports, upper back former support with laterally adjustable back former support bearing plate, 2 back formers, bending formers St or V. In sturdy carrying case.

Description	Art.-No.
Set St ¾-½-¾-1-1¼"	590020
Set St ½-¾-1-1¼-1½-2"	590021
Set V 40-50-63 mm	590022

Accessories

Description	Art.-No.
Drive unit with back former supports and back formers	590000
Slide piece Ø 75 mm (pack of 2)	590111
Tripod	590150
Carrying case with practical handles	590160
Angle gauge for dimensionally accurate bending	590153

Bending former for pipes Ø mm/inch	Bending radius ¹⁾ mm	Bending radius ²⁾ mm	suitable for				Art.-No.
			St 10255	>			
St ¾"	50		•				590051
St ½"	65		•				590052
St ¾"	85		•				590053
St 1"	100		•				590054
St 1¼"	150		•				590055
St 1½"	170		•				590056
St 2"	220		•				590057
V 32 mm	112	128		•			590061
V 40 mm	140	160		•			590058
V 50 mm	175	200		•			590059
V 63 mm	220	252		•			590060
V 75 mm	260	298		▲			590062

St 10255: Steel pipes (threaded pipes) EN 10255
V: multilayer composite pipes of the pressfitting systems
▲ 2 slide pieces Ø 75 mm (Art. No. 590111) required

¹⁾ Bending radius mm on the inside of the bend (EN 10255)

²⁾ Bending radius mm at the neutral axis of the bend (DVGW VP 632)

