



Basic-Pack

### Supply format

**REMS Curvo Set.** Electric pipe and tube bender Ø 10–40 mm, Ø ¼–1½", up to 180°. Hard, semi-hard, soft copper pipes, also thin-walled, Ø 10–35 mm, Ø ⅜–1½", soft coated copper pipes, also thin-walled, Ø 10–18 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ⅜–1½", pipes of the press fitting systems of stainless steel Ø 12–28 mm, carbon steel, also coated, Ø 12–28 mm, soft precision steel pipes Ø 10–28 mm, steel pipes EN 10255 Ø ¼–¾", electrical installation pipes EN 50086 Ø 16–32 mm, composite tubes Ø 14–40 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50–60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation, insert bolt. Bending formers and back formers. In sturdy steel case.

Description	Art.-No.
<b>Set 15-18-22</b>	580026
<b>Set 15-18-22-28<sup>1)</sup></b>	580027
<b>Set 15-18-22-28<sup>2)</sup></b>	580036
<b>Set 15-18-22-28<sup>3)</sup></b>	580035
<b>Set 12-15-18-22</b>	580020
<b>Set 12-15-18-22-28<sup>1)</sup></b>	580033
<b>Set 12-15-18-22-28<sup>2)</sup></b>	580037
<b>Set 15-22-28<sup>1)</sup></b>	580022
<b>Set 15-22-28<sup>2)</sup></b>	580040
<b>Set 17-20-24</b>	580023
<b>Set 12-14-16-18-22</b>	580021
<b>Set 12-14-16-18-22-28<sup>1)</sup></b>	580031
<b>Set 12-14-16-18-22-28<sup>2)</sup></b>	580038
<b>Set 14-16-18-22-28<sup>1)</sup></b>	580028
<b>Set 14-16-18-22-28<sup>2)</sup></b>	580039
<b>Set ⅜-1½-⅔-¾-⅞"</b>	580024
<b>Set 16-20-26-32</b>	580025
<b>Set 16-20-25-32</b>	580034
<b>Set 20-25-32</b>	580029
<b>Set 32-40</b>	580030
<b>Basic-Pack (without bending and back formers)</b>	580010

REMS Curvo Set delivered with the smaller radius bending and back former (except Art.-No. 580029 and 580030), see page 131.

- <sup>1)</sup> Bending former and back former 28, R102, Art. No. 581070, for hard, semi-hard copper pipes, also thin-walled. See page 131.
- <sup>2)</sup> Bending former and back former 28, ¾" (DN 20), R102, Art. No. 581260, for hard copper pipes Ø 28 mm, Ø 1½", pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". See page 131.
- <sup>3)</sup> Bending former and back former 28, ¾" (DN 20), R114, Art. No. 581310, for hard, semi-hard copper pipes Ø 28 mm, pipes of the press fitting systems of stainless steel/carbon steel Ø 28 mm, steel pipes ¾". According to DVGW work sheet GW 392 for hard and semi-hard copper pipes Ø 28 mm minimum bending radius 114 mm necessary. Wall thickness ≥ 0.9 mm. See page 131.

### Accessories

Description	Art.-No.
Bending formers and back formers see page 131.	
<b>REMS Curvo drive unit</b>	580000
<b>Insert bolt</b>	582036
<b>REMS bending spray, 400 ml</b>	140120
<b>Steel case with insert</b>	586000
<b>Machine support 3B, height adjustable, on tripod</b>	586100
<b>Machine support WB, height adjustable, for mounting on work bench</b>	586150

