

### Supply format

**REMS Curvo 50 Basic-Pack.** Electric pipe and tube bender Ø 10–50 mm, up to 90°. Steel pipes EN 10255 Ø ¼–1¼", stainless steel pipes EN ISO 1127, EN 10217-7, Ø ½–1½", s ≤ 2.6 mm, hard, semi-hard, soft copper pipes, Ø 10–42 mm, thin-walled copper pipes Ø 10–35 mm, thick-walled copper pipes K65 for refrigeration and air conditioning technology EN 12735-1 Ø ¾–1½", pipes of the press fitting systems of stainless steel Ø 12–42 mm, carbon steel Ø 12–42 mm, coated carbon steel Ø 12–28 mm, composite tubes Ø 14–50 mm, etc. Drive unit with maintenance-free gear and safety slipping clutch, universal motor 230 V or 110 V, 50–60 Hz, 1000 W, stepless electronic safety switch, right and left-hand rotation. Adaptor block 35–50, Support 35–50, insert bolt. In sturdy carrying case.

	Art.-No.
	580110

Other voltages on request.



### Accessories

Description	Art.-No.
<b>Bending formers and back formers</b> see page 131.	
<b>REMS Curvo 50 drive unit</b>	580100
<b>Adaptor block 35–50, Support 35–50</b> , for bending formers and back formers Ø 35 R 100, Ø 42 R 140, Ø 50 R 135, Ø 1" R 100, Ø 1 ¼" R 140 (see page 131).	582110
<b>Adaptor block 10–40, Support 10–40</b> , for bending formers and back formers REMS Curvo, REMS Akku-Curvo, REMS Sinus (see page 131).	582120
<b>Insert bolt</b>	582036
<b>REMS bending spray, 400 ml</b>	140120
<b>Carrying case with practical handles</b>	590160
<b>Steel case</b> with insert for each bending former and back former R 100 and R 135/R 140, 90°	586012

