



Supply format

REMS Mini-Press S 22V ACC Basic-Pack. Cordless radial press with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø ¾–1 ¼". For operating with REMS pressing tongs Mini/pressing rings. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 230 V or 110 V, 50–60 Hz, 70 W.

Version	Art.-No.
In sturdy steel case.	578015
In L-Boxx system case.	578016

Other voltages on request.

Accessories

Description	Art.-No.
REMS pressing tongs Mini/pressing rings see page 140–154.	
REMS cropping tongs Mini for threaded rods see page 155.	
REMS Mini-Press S 22V ACC drive unit, without battery	578003
Battery Li-Ion 21.6V, 1.5Ah	571570
Battery Li-Ion 21.6V, 2.5Ah	571571
Battery Li-Ion 21.6V, 5.0Ah	571581
Battery Li-Ion 21.6V, 9.0Ah	571583
Rapid charger Li-Ion 230V, 50–60Hz, 90W	571585
Rapid charger Li-Ion 230V, 50–60Hz, 300W	571587
Voltage supply Li-Ion 230 V/21.6 V, 15A for mains operation 230 V instead of battery Li-Ion 21.6 V.	571567
Steel case with inlay	578290
L-Boxx system case with inserts	578299

