

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press)
and suitable radial presses of other makes

System	Pressing contour	Art.-No.
Geberit Mapress EDELSTAHL	M 12	570100
	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 35 (PR-3S) ³⁾	572727
	M 42 (PZ-4G)	570160
	M 54 (PZ-4G)	570170
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 12 45° (PR-2B) ³⁾	574520
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
Geberit Mapress EDELSTAHL Gas	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 35 (PR-3S) ³⁾	572727
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7) 9)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7) 9)}	579111
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (P R-2B) ³⁾	574530
Geberit Mapress KUPFER	M 12	570100
	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 35 (PR-3S) ³⁾	572727
	M 42 (PZ-4G)	570160
	M 54 (PZ-4G)	570170
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 66,7 XL (PR-3S) ^{3) 7)}	579107
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 12 45° (PR-2B) ³⁾	574520
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
Geberit Mapress KUPFER Gas	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 35 (PR-3S) ³⁾	572727
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
Geberit Mepla	G 16*	570400
	G 20*	570410
	G 26*	570420
	G 32	570430
	G 40	570440
	G 50	570450
	G 63 (PZ-S)	572470

System	Pressing contour	Art.-No.
Geberit Mepla Therm	G 16*	570400
	G 20*	570410
	G 26*	570420
Geberit Volex	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
General Fittings 5T00	H 16*	570320
	H 20*	570350
	H 26*	570370
	H 32	570380
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	U 16*	570765
	U 20*	570775
	U 32	570785
General Fittings Serie 5S00	B 16*	570850
	B 18*	570855
	B 20*	570860
	B 26	570870
	B 32	570880
	F 16*	570717
	F 20*	570727
	F 26*	570730
	F 32	570735
	F 16 45° (PR-2B) ³⁾	574550
	F 20 45° (PR-2B) ³⁾	574552
	F 26 45° (PR-2B) ³⁾	574554
General Fittings Trident	F 32 45° (PR-2B) ³⁾	574556
	H 16*	570320
	H 18*	570340
	H 20*	570350
	H 25*	570360
	H 26*	570370
	H 32	570380
	H 40 (PZ-4G)	570390
	TH 16*	570460
	TH 18*	570465
	TH 20*	570470
	TH 25*	570495
	TH 26*	570475
General Fittings Trident	TH 32	570480
	TH 40	570485
	TH 50 (PZ-S)	572400
	TH 63 (PZ-S)	572405
	U 16*	570765
	U 18*	570770
	U 20*	570775
	U 25*	570780
	U 32	570785
	U 40	570790
	U 63 (PZ-S)	572365
	U 63 (PR-3B) ³⁾	572837
General Fittings Trident Gas	B 16*	570850
	F 16*	570717
	F 16 45° (PR-2B) ³⁾	574550
	H 16*	570320
	H 20*	570350
	H 26*	570370
	H 32	570380
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	U 16*	570765
	U 20*	570775
	U 32	570785

System	Pressing contour	Art.-No.
Giacomini	H 16*	570320
Raccordi RM	H 20*	570350
Giacomini	H 26*	570370
	H 32	570380
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	U 16*	570765
	U 20*	570775
	U 32	570785
	U 40	570790
	U 50	570795
	U 63 (PZ-S)	572365
	U 63 (PZ-S)	572365
Giacomini RM MULTIGAS	H 16*	570320
	H 20*	570350
	H 26*	570370
	H 32	570380
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	U 16*	570765
	U 20*	570775
	U 32	570785
	V 15	570115
	V 18	570125
Giacomini Valvole Giacomini serie R850V	V 22	570135
	V 28	570145
	V 35	570155
	V 42	570165
	V 54	570175
	V 15 45° (PR-2B) ³⁾	574504
	V 18 45° (PR-2B) ³⁾	574506
	V 22 45° (PR-2B) ³⁾	574508
	V 28 45° (PR-2B) ³⁾	574510
	V 35 45° (PR-2B) ³⁾	574512
	SA 15	570935
	SA 18	570940
	SA 22	570945
Golan Pipe Systems (Scandinavia) Alu-Pres	SA 28	570950
	SA 35	570955
	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
	U 16*	570765
Grinnell G-PRESS Copper Fittings	U 20*	570775
	U 25*	570780
	U 32	570785
	U 40	570790
	U 50	570795
	U 63 (PZ-S)	572365
	U 63 (PR-3B) ³⁾	572837
	U 75 (PR-3B) ³⁾	572828
	VUS ½" (OD 15,9mm)	571770
	VUS ¾" (OD 22,2mm)	571775
	VUS 1" (OD 28,6mm)	571780
	VUS 1¼" (OD 34,9mm)	571785
	VUS 1½" (OD 41,3mm)	571790
Alu-Pres	VUS 2" (OD 54,0mm)	571795
	VUSFz 2½" (PR-3B) ³⁾	572819
	(OD 66,7mm)	
	VUSFz 3" (PR-3B) ³⁾	572820
	(OD 79,4mm)	
	VUSFz 4" (PR-3B) ³⁾	572821
	(OD 104,8mm)	

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.
Observe the national regulations.

* These pressing tongs also fit the manual radial press REMS Eco-Press. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For this pressfitting system producing a pressing joint with manual radial presses is not permitted.
- Adapter tongs are required for driving pressing rings (PR), see page 192.
- Press fittings made of red bronze (ProPress XL) must be pressed with pressing rings with press contour VUSR, copper fittings (ProPress XL-C) and stainless steel fittings (ProPress XL-S) with pressing rings with press contour VUSF.
- For taking suitable pressing inserts.
- Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.
- Driven by REMS Power-Press XL and REMS Akku-Press XL 45 kN 22V ACC.
- Thrust force 45 kN required. Can only be driven by REMS Akku-Press XL 45kN 22V ACC.
- Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

The suitability of REMS pressing tools for pressfitting systems: Date 15.10.2019. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

Pressing tongs/pressing rings for additional pressfitting systems on request.