

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press) and suitable radial presses of other makes

System	Pressing contour	Art.-No.
Pegler Yorkshire	M 15	570110
XPress	M 18 ¹⁾	570120
Stainless	M 22	570130
	M 28 ¹⁾	570140
	M 35	570150
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
Pegler Yorkshire	M 15	570110
XPress Stainless	M 18 ¹⁾	570120
Gas	M 22	570130
	M 28 ¹⁾	570140
	M 35	570150
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
PERFEXIM	U 16*	570765
"PERFEKT SYSTEM"	U 20*	570775
	U 25*	570780
	U 32	570785
PERFILTUBO	U 16*	570765
PERFILALUPEX	U 18*	570770
	U 20*	570775
	U 25*	570780
	U 32	570785
	U 40	570790
	U 50	570795
	U 63 (PR-3B) ³⁾	572837
	U 63 (PZ-S)	572365
	U 75 (PR-3B) ³⁾	572828
PERFILTUBO	M 15	570110
PERFILPRESS	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530
PEXTUBE	RFz 16*	571325
PexTube	RFz 20*	571330
	RFIz 25	571337
	RFIz 32	571342
Pipelife	M 15	570110
C-PRESS	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530

System	Pressing contour	Art.-No.
Pipelife	TH 16*	570460
RADOPRESS	TH 18*	570465
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	TH 40	570485
	TH 50 (PZ-S)	572400
	TH 63 (PZ-S)	572405
Pipetec Connect	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	TH 40	570485
	TH 50 (PZ-S)	572400
	TH 63 (PZ-S)	572405
PLASTICA ALFA	TH 16*	570460
Multiplex	TH 20*	570470
	TH 26*	570475
	TH 32	570480
PLASTICA ALFA	TH 16*	570460
Multiplex Air	TH 20*	570470
	TH 26*	570475
	TH 32	570480
PLASTICA ALFA	TH 16*	570460
Multiplexalfa Gas	TH 20*	570470
	TH 26*	570475
PLASTICA ALFA	TH 16*	570460
Multiplexalfa Gas protek	TH 20*	570470
	TH 26*	570475
PLASTICA ALFA	TH 16*	570460
Multiplex	TH 20*	570470
Plus	TH 26*	570475
	TH 32	570480
PLASTICA ALFA	TH 16*	570460
Multiplex	TH 20*	570470
Thermo	TH 26*	570475
	TH 32	570480
PLASTICA ALFA	TH 16*	570460
Multiplex	TH 20*	570470
Thermo Plus	TH 26*	570475
	TH 32	570480
PLÁSTICOS	U 16*	570765
FERRO	U 20*	570775
FERROPLAST	U 25*	570780
GPF MC PRESS	U 32	570785
Pressfitting MULTICAPA		
PLÁSTICOS	U 16*	570765
FERRO	U 20*	570775
FERROPLAST	U 25*	570780
GPF PPSU	U 32	570785
Pressfitting PE-X y MULTICAPA		
PLÁSTICOS	RFz 16*	571325
FERRO	RFz 20*	571330
FERROPLAST	RFz 25	571335
GPF PRESS	RFz 32	571340
Pressfitting PE-X		
PLUMBING PLUS	K16/P18*	572600
EZIPRESS Crimp (AUS)	K/20*	572605
	K/25*	572610
	K32	572615
	K1/40	572620
	K1/50	572625
PLUMBING PLUS	K16/P18*	572600
EZIPRESS Gas (AUS)	K/20*	572605
	K/25*	572610
	K32	572615
	K1/40	572620
	K1/50	572625

System	Pressing contour	Art.-No.
PLUMBING PLUS	VAU 15 (OD 12,7 mm)	572687
EZIPRESS Gas (AUS)	VAU 20 (OD 19,1 mm)	572689
	VAU 25 (OD 25,4 mm)	572691
	VAU 32 (OD 31,8 mm)	572693
	VAU 40 (OD 38,1 mm)	572695
	VAU 50 (OD 50,8 mm)	572697
	VAUFz 65 (PR-3B) ³⁾	572839
	(OD 63,5 mm)	
	VAUFz 80 (PR-3B) ³⁾	572840
	(OD 76,2 mm)	
	VAUFz 100 (PR-3B) ³⁾	572841
	(OD 101,6 mm)	
	VAU 15 45° (PR-2B) ³⁾	574540
	(OD 12,7 mm)	
	VAU 20 45° (PR-2B) ³⁾	574542
	(OD 19,1 mm)	
	VAU 25 45° (PR-2B) ³⁾	574544
	(OD 25,4 mm)	
PLUMBING PLUS	VAU 15 (OD 12,7 mm)	572687
EZIPRESS Solar (AUS)	VAU 20 (OD 19,1 mm)	572689
	VAU 25 (OD 25,4 mm)	572691
	VAU 32 (OD 31,8 mm)	572693
	VAU 40 (OD 38,1 mm)	572695
	VAU 50 (OD 50,8 mm)	572697
	VAUFz 65 (PR-3B) ³⁾	572839
	(OD 63,5 mm)	
	VAUFz 80 (PR-3B) ³⁾	572840
	(OD 76,2 mm)	
	VAUFz 100 (PR-3B) ³⁾	572841
	(OD 101,6 mm)	
	VAU 15 45° (PR-2B) ³⁾	574540
	(OD 12,7 mm)	
	VAU 20 45° (PR-2B) ³⁾	574542
	(OD 19,1 mm)	
	VAU 25 45° (PR-2B) ³⁾	574544
	(OD 25,4 mm)	
PLUMBING PLUS	VAU 15 (OD 12,7 mm)	572687
EZIPRESS Water (AUS)	VAU 20 (OD 19,1 mm)	572689
	VAU 25 (OD 25,4 mm)	572691
	VAU 32 (OD 31,8 mm)	572693
	VAU 40 (OD 38,1 mm)	572695
	VAU 50 (OD 50,8 mm)	572697
	VAUFz 65 (PR-3B) ³⁾	572839
	(OD 63,5 mm)	
	VAUFz 80 (PR-3B) ³⁾	572840
	(OD 76,2 mm)	
	VAUFz 100 (PR-3B) ³⁾	572841
	(OD 101,6 mm)	
	VAU 15 45° (PR-2B) ³⁾	574540
	(OD 12,7 mm)	
	VAU 20 45° (PR-2B) ³⁾	574542
	(OD 19,1 mm)	
	VAU 25 45° (PR-2B) ³⁾	574544
	(OD 25,4 mm)	
POLYPIPE	TH 10*	570467
POLYSURE	TH 15*	570457
	TH 22*	570472
	TH 28	570477
POLYSAN	M 15	570110
Handelsges.	M 18	570120
m.b.H. & Co KG	M 22	570130
(Krems/Öster-reich)	M 28	570140
	M 35	570150
POLYSAN-	M 42 (PR-3S) ³⁾	572706
C-Stahl-Press-	M 54 (PR-3S) ³⁾	572708
System M	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow. Observe the national regulations.

* These pressing tongs also fit the manual radial press REMS Eco-Press. Observe the national regulations.

- Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.
- For this pressfitting system producing a pressing joint with manual radial presses is not permitted.
- Adapter tongs are required for driving pressing rings (PR), see page 192.
- Press fittings made of red bronze (ProPress XL) must be pressed with pressing rings with press contour VUSR, copper fittings (ProPress XL-C) and stainless steel fittings (ProPress XL-S) with pressing rings with press contour VUSF.
- For taking suitable pressing inserts.
- Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.
- Driven by REMS Power-Press XL and REMS Akku-Press XL 45 kN 22V ACC.
- Thrust force 45 kN required. Can only be driven by REMS Akku-Press XL 45kN 22V ACC.
- Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

The suitability of REMS pressing tools for pressfitting systems: Date 15.10.2019. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

Pressing tongs/pressing rings for additional pressfitting systems on request.