

REMS pressing tongs

REMS pressing rings

Accessories for REMS radial presses (except for REMS Mini-Press)
and suitable radial presses of other makes

System	Pressing contour	Art.-No.
V		
Valsir Bravopress	B 16*	570850
	B 20*	570860
	B 26	570870
	B 32	570880
	F 16*	570717
	F 20*	570727
	F 26*	570730
	F 16 45° (PR-2B) ³⁾	574550
	F 20 45° (PR-2B) ³⁾	574552
	F 26 45° (PR-2B) ³⁾	574554
	H 16*	570320
	H 20*	570350
	H 26*	570370
	H 32	570380
	H 32 V	570685
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	U 16*	570765
	U 20*	570775
	C 26*	570750
	U 32	570785
Valsir PEXAL	H 14*	570310
	H 16*	570320
	H 20*	570350
	H 26*	570370
	H 32	570380
	H 32 V	570685
	TH 16*	570460
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	TH 40	570485
	TH 50 (PZ-S)	572400
	TH 63 (PZ-S)	572405
	U 16*	570765
	U 20*	570775
	C 26*	570750
	U 32	570785
	U 40	570790
	U 50	570795
	U 63 (PR-3B) ³⁾	572837
	U 63 (PZ-S)	572365
	U 75 (PR-3B) ³⁾	572828
Van Marcke NV Tubipex	TH 16*	570460
	TH 17*	570462
	TH 20*	570470
	TH 26*	570475
	TH 32	570480
	TH 40	570485
	TH 50 (PZ-S)	572400
	TH 63 (PZ-S)	572405
	THz 75 (PR-3B) ³⁾	572829
Van Marcke NV Tubipress	M 12	570100
	M 15	570110
	M 18	570120
	M 22	570130
	M 28	570140
	M 35	570150
	M 42 (PZ-4G)	570160
	M 54 (PZ-4G)	570170
	M 42 (PR-3S) ³⁾	572706
	M 54 (PR-3S) ³⁾	572708
	M 76,1 XL (PR-3S) ^{3) 7)}	579101
	M 88,9 G XL (PR-3S) ^{3) 7)}	579110
	M 108,0 G XL (PR-3S) ^{3) 7)}	579111
	M 12 45° (PR-2B) ³⁾	574520
	M 15 45° (PR-2B) ³⁾	574522
	M 18 45° (PR-2B) ³⁾	574524
	M 22 45° (PR-2B) ³⁾	574526
	M 28 45° (PR-2B) ³⁾	574528
	M 35 45° (PR-2B) ³⁾	574530

System	Pressing contour	Art.-No.
Variotherm	TH 11,6*	570482
System TH	TH 16*	570460
	TH 20*	570470
VESBO	U 16*	570765
VPREMIUM	U 20*	570775
	U 25*	570780
	U 32	570785
	U 40	570790
	U 50	570795
	U 63 (PZ-S)	572365
Viega	VX 12*	571630
Fonterra	VP 14/15*	570905
	VP 16/17*	570910
	VP 20*	570915
	VP 25	570920
Viega MegaPress	VMP ¾" (OD 17,2 mm)	571740
	VMP ½" (OD 21,3 mm)	571762
	VMPz ¾" (OD 26,9 mm)	571764
	VMPz 1" (OD 33,7 mm)	571767
	VMPz 1¼" (PZ-S) (OD 42,4 mm)	572413
	VMPz 1½" (PR-3B) ³⁾ (OD 48,3 mm)	572844
	VMPz 2" (PR-3B) ³⁾ (OD 60,3 mm)	572845
Viega Pexfit	VX 16*	571635
	VX 20*	571640
	VX 25*	571645
Viega Pexfit G	VX 16*	571635
	VX 20*	571640
	VX 25*	571645
Viega Prestabo	V 12	570107
	V 15	570115
	V 18	570125
	V 22	570135
	V 28	570145
	V 35	570155
	V 42	570165
	V 54	570175
	VFz 64,0 (PR-3B) ^{3) 6)}	572815
	VFz 76,1 (PR-3B) ^{3) 6)}	572816
	VFz 88,9 (PR-3B) ^{3) 6)}	572817
	VFz 108,0 (PR-3B) ^{3) 6)}	572818
	V 12 45° (PR-2B) ³⁾	574502
	V 15 45° (PR-2B) ³⁾	574504
	V 18 45° (PR-2B) ³⁾	574506
	V 22 45° (PR-2B) ³⁾	574508
	V 28 45° (PR-2B) ³⁾	574510
	V 35 45° (PR-2B) ³⁾	574512
Viega Profipress	V 12	570107
	VG 14	570132
	V 15	570115
	VG 16	570137
	V 18	570125
	V 22	570135
	V 28	570145
	V 35	570155
	V 42	570165
	V 54	570175
	VFz 64,0 (PR-3B) ^{3) 6)}	572815
	VFz 76,1 (PR-3B) ^{3) 6)}	572816
	VFz 88,9 (PR-3B) ^{3) 6)}	572817
	VFz 108,0 (PR-3B) ^{3) 6)}	572818
	V 12 45° (PR-2B) ³⁾	574502
	VG 14 45° (PR-2B) ³⁾	574536
	V 15 45° (PR-2B) ³⁾	574504
	VG 16 45° (PR-2B) ³⁾	574538
	V 18 45° (PR-2B) ³⁾	574506
	V 22 45° (PR-2B) ³⁾	574508
	V 28 45° (PR-2B) ³⁾	574510
	V 35 45° (PR-2B) ³⁾	574512

System	Pressing contour	Art.-No.
Viega	V 12	570107
Profipress G	VG 14	570132
	V 15	570115
	VG 16	570137
	V 18	570125
	V 22	570135
	V 28	570145
	V 35	570155
	V 42	570165
	V 54	570175
	VFz 64,0 (PR-3B) ^{3) 6)}	572815
	V 12 45° (PR-2B) ³⁾	574502
	VG 14 45° (PR-2B) ³⁾	574536
	V 15 45° (PR-2B) ³⁾	574504
	VG 16 45° (PR-2B) ³⁾	574538
	V 18 45° (PR-2B) ³⁾	574506
	V 22 45° (PR-2B) ³⁾	574508
	V 28 45° (PR-2B) ³⁾	574510
	V 35 45° (PR-2B) ³⁾	574512
Viega Profipress S	V 12	570107
	V 15	570115
	V 18	570125
	V 22	570135
	V 28	570145
	V 35	570155
Viega Profipress Therm	V 12 45° (PR-2B) ³⁾	574502
	V 15 45° (PR-2B) ³⁾	574504
	V 18 45° (PR-2B) ³⁾	574506
	V 22 45° (PR-2B) ³⁾	574508
	V 28 45° (PR-2B) ³⁾	574510
	V 35 45° (PR-2B) ³⁾	574512
Viega ProPress System USA	VUS ½" (OD 15,9 mm)	571770
	VUS ¾" (OD 22,2 mm)	571775
	VUS 1" (OD 28,6 mm)	571780
	VUS 1¼" (OD 34,9 mm)	571785
	VUS 1½" (OD 41,3 mm)	571790
	VUS 2" (OD 54,0 mm)	571795
XL-C/XL-S	VUSFz 2½" (PR-3B) ^{3) 6)} (OD 66,7 mm)	572819
XL-C/XL-S	VUSFz 3" (PR-3B) ^{3) 6)} (OD 79,4 mm)	572820
XL-C/XL-S	VUSFz 4" (PR-3B) ^{3) 6)} (OD 104,8 mm)	572821
Viega ProPress WATER System AUS	VAU 15 (OD 12,7 mm)	572687
	VAU 20 (OD 19,1 mm)	572689
	VAU 25 (OD 25,4 mm)	572691
	VAU 32 (OD 31,8 mm)	572693
	VAU 40 (OD 38,1 mm)	572695
	VAU 50 (OD 50,8 mm)	572697
Viega ProPressG GAS System AUS	VAU 15 (OD 12,7 mm)	572687
	VAU 20 (OD 19,1 mm)	572689
	VAU 25 (OD 25,4 mm)	572691
	VAU 32 (OD 31,8 mm)	572693
	VAU 40 (OD 38,1 mm)	572695
	VAU 50 (OD 50,8 mm)	572697

Pressfitting systems for gas installations must only be pressed with pressing tongs/pressing rings which are highlighted in yellow.

Observe the national regulations.

* These pressing tongs also fit the manual radial press REMS Eco-Press. Observe the national regulations.

¹⁾ Only pressing tongs from designation "108" (1st quarter of 2008), "208" (2nd quarter of 2008) etc. can be used. The designation is stamped on every pressing jaw.

²⁾ For this pressfitting system producing a pressing joint with manual radial presses is not permitted.

³⁾ Adapter tongs are required for driving pressing rings (PR), see page 192.

⁴⁾ Press fittings made of red bronze (ProPress XL) must be pressed with pressing rings with press contour VUSR, copper fittings (ProPress XL-C) and stainless steel fittings (ProPress XL-S) with pressing rings with press contour VUSF.

⁵⁾ For taking suitable pressing inserts.

⁶⁾ Press fittings made of red bronze (Sanpress XL) must be pressed with pressing rings with press contour VR, copper fittings (Profipress XL, Profipress G XL), carbon steel (Prestabo XL) and stainless steel fittings (Sanpress Inox XL, Sanpress Inox G XL) with pressing rings with press contour VF.

⁷⁾ Driven by REMS Power-Press XL and REMS Akku-Press XL 45 kN 22V ACC.

⁸⁾ Thrust force 45 kN required. Can only be driven by REMS Akku-Press XL 45kN 22V ACC.

⁹⁾ Use pressing rings labelled "M 88.9 G" or "M 108 G" on the three pressing segments for gas installations.

The suitability of REMS pressing tools for pressfitting systems: Date 15.10.2019. For the updated situation regarding suitability status check our website:

www.rems.de → Downloads → Product catalogues, brochures → REMS Catalogue.

Pressing tongs/pressing rings for additional pressfitting systems on request.