

REMS Ax-Press 30 22 V

Cordless axial press

Compact, handy electric tool for producing compression sleeve joints with crimping sleeve. For trade and industry. For the building site and the workshop. Li-Ion 22 V Technology. For battery and corded operation.

Axial compression Ø 12–32 mm

REMS Ax-Press 30 22 V – up to Ø 32 mm. Ultra light, ultra small, ultra handy, ultra fast. Li-Ion 21.6 V, 1.5 Ah battery for approx. 130 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge.

Compression heads for all common systems

Complete assortment of REMS compression heads for all common compression sleeve systems with crimping sleeve. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and correspond to the respective compression sleeve system. Thus perfect system-conformity, safe jointing.

Design

Compact, handy, light. Drive unit with battery only 4.6 kg. Vertically from the drive unit located pressing device for seating the compression heads (Patent US 6,415,641). Can be used anywhere, free hand, over head, in confined spaces. Optimum weight distribution for one-hand operation. Drive unit with inserted compression heads can be put down on the battery ready to pick up. Ergonomically designed housing with soft grip. LED work light for illuminating the work place. Compression heads and expander heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

High pressing force for perfect pressing in seconds, e.g. Ø 26 mm in only 5 s. Thrust force 30 kN. Powerful electro-hydraulic drive, eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22 V Technology. Highly resistant Li-Ion 21.6 V battery with 1.5, 2.5, 5.0 or 9.0 Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 1.5 Ah battery for approx. 130 pressings, 2.5 Ah for approx. 220 pressings, 5.0 Ah for approx. 430 pressings, 9.0 Ah for approx. 780 pressings Georg Fischer pfci ALUPEX-EXPRESS Ø 16 mm with one battery charge. Graduated charging state display with coloured LED. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger Li-Ion 230 V, 50–60 Hz, 70 W. Rapid charger Li-Ion 230 V, 50–60 Hz, 300 W, for shorter charging times, as accessory. Li-Ion 230 V/21.6 V, 15 A voltage supply for mains operation 230 V instead of Li-Ion battery 21.6 V, as accessory.

Supply format

REMS Ax-Press 30 22 V Basic-Pack. Cordless axial press for producing compression sleeve joints with crimping sleeve Ø 12–32 mm. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 230 V, 50–60 Hz, 70 W. In sturdy steel case.

Art.-No.

573018

Accessories

| Description | Art.-No. |
|--|----------|
| REMS Ax-Press 30 22 V drive unit, without battery | 573008 |
| Battery Li-Ion 21.6 V, 1.5 Ah | 571570 |
| Battery Li-Ion 21.6 V, 2.5 Ah | 571571 |
| Battery Li-Ion 21.6 V, 5.0 Ah | 571581 |
| Battery Li-Ion 21.6 V, 9.0 Ah | 571583 |
| Rapid charger Li-Ion 230 V, 50–60 Hz, 90 W | 571585 |
| Rapid charger Li-Ion 230 V, 50–60 Hz, 300 W | 571587 |
| Voltage supply Li-Ion 230 V/21.6 V, 15 A for mains operation 230 V instead of battery Li-Ion 21.6 V. | 571567 |
| Steel case with insert | 573282 |

REMS compression heads

| Compression sleeve system | Compression head | Art.-No. |
|---|-------------------|----------|
| Brasstech Raptor/ Metalfex/ Raptor 2/ MULTItermoSAN | ME 14 (pack of 2) | 573100 |
| | ME 16 (pack of 2) | 573102 |
| | ME 20 (pack of 2) | 573106 |
| | ME 26 (pack of 2) | 573108 |
| | ME 32 (pack of 2) | 573110 |
| General Fittings Serie 5400 | ME 14 (pack of 2) | 573100 |
| | ME 16 (pack of 2) | 573102 |
| | ME 20 (pack of 2) | 573106 |
| | ME 26 (pack of 2) | 573108 |
| | ME 32 (pack of 2) | 573110 |



German Quality Product

Tested by electrouisse ➤



Info



REMS compression heads

| Compression sleeve system | Compression head | Art.-No. |
|--|-------------------|----------|
| Georg Fischer pfci ALUPEX-EXPRESS/ Alupex Gas System | ME 16 (pack of 2) | 573102 |
| | ME 20 (pack of 2) | 573106 |
| | ME 26 (pack of 2) | 573108 |
| | ME 32 (pack of 2) | 573110 |
| Logstor | ME 16 (pack of 2) | 573102 |
| | LR 20 (pack of 2) | 573430 |
| | LR 22 (pack of 2) | 573432 |
| | LR 25 (pack of 2) | 573434 |
| | LR 28 (pack of 2) | 573436 |
| | LR 32 (pack of 2) | 573438 |