

Universal manual axial press for producing compression sleeve joints.

Axial compression Ø 12–32 mm

**REMS Ax-Press HK – universal up to Ø 22 mm**  
Ultra small, ultra light, ultra handy. Only 1.1 kg

**REMS Ax-Press H – universal up to Ø 32 mm.**  
Handy and light. Only 1.4 kg.

**Complete assortment of REMS compression heads, quickly interchangeable.**

### System advantage

Only **one** type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22 V ACC, REMS Ax-Press 25 L 22 V ACC. Thus easy, economic stocking.

### Compression heads

Full range of REMS compression heads for all common compression sleeve systems (page 202–203). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

### Twin compression heads


REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (**Patent DE pending**) (page 202). No need to change compression heads. Extremely simple, saves time.

### Design

Compact, job site proven. Handy and light. REMS Ax-Press HK drive unit only 1.1 kg. REMS Ax-Press H drive unit only 1.4 kg. Works anywhere, free-hand, also in tight spots. 66 mm stroke. Quick-acting forward and release for easy, fast operation. Selectable compression head position (**Patent ES 2 273 563, Patent FR 05 03513, Patent DE pending**) for pressing compression sleeve connectors with a clamping distance of ≤ 161 mm in one action and for double pressings. Quick-change compression heads and pressing inserts without tools. Secure fit of compression heads and pressing inserts by spring catch. REMS Ax-Press H with overload protection.

### Expanding

Various pipe expanders and complete range of REMS expanding heads for all common compression sleeve systems (page 207–211).



German Quality Product

### Supply format

**REMS Ax-Press HK drive unit.** Axial press for single-handed operation for producing compression sleeve joints Ø 12–22 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	
	574302	

### Supply format

**REMS Ax-Press H drive unit.** Manual axial press for producing compression sleeve joints Ø 12–32 mm. 66 mm stroke. With quick-acting forward and release. For driving REMS compression heads. In a carton.

	Art.-No.	
	574300	



### Accessories

Description	Art.-No.	
<b>REMS compression heads</b> see page 202–203.		
<b>Carrying bag</b> for REMS Ax-Press HK/H drive unit and compression heads	574437	
<b>Case</b> with inlay for REMS Ax-Press HK drive unit and compression heads	574352	

