

REMS Ax-Press 25 22V ACC

REMS Ax-Press 25 L 22V ACC

Compact, handy power tool with automatic return for manufacturing compression sleeve joints. Li-Ion 22V Technology. For battery and corded operation. For trade and industry. For the building site and the workshop.

Axial compression

Ø 12–40 mm

REMS Ax-Press 25 22V ACC – universal up to Ø 40 mm. Super light, super handy. Fast. With automatic return. Optimum weight distribution for single-hand operation. Swivelling compression device. Li-Ion 21.6 V, 1.5 Ah battery for approx. 300 pressings REHAU RAUTITIAN PX Ø 16 mm with one battery charge.

System advantage

Only one type of compression heads for REMS Ax-Press HK, REMS Ax-Press H, REMS Ax-Press 25 22V ACC, REMS Ax-Press 25 L 22V ACC. Thus easy, economic stocking.

Compression heads for all common systems

Full range of REMS compression heads for all common compression sleeve systems (page 202–203). Choice of REMS compression heads with spring lock for seating common compression inserts. High-grade compression heads in forged and specially hardened steel. The REMS compression heads are system-specific and meet the demands of compression sleeve systems. Thus perfect system-conformity, safe jointing.

Twin compression heads

REMS twin compression heads with two holders each which interleave, for pipe unions of different dimensions (**Patent DE pending**) (page 202). No need to change compression heads. Extremely simple, saves time.

Design

Compact, handy, light. REMS Ax-Press 25 22V ACC drive machine with battery weighs only 3.0 kg, only 28 cm long REMS Ax-Press 25 L 22V ACC drive machine with battery weighs only 3.2 kg, only 31 cm long REMS Ax-Press 25 22V ACC and REMS Ax-Press 25 L 22V ACC with 40 mm stroke respectively REMS Ax-Press 25 22V ACC with preset compression head position for pressing compression sleeve connectors with a clamping distance ≤ 82 mm in one action REMS Ax-Press 25 L 22V ACC with selectable compression head position for pressing compression sleeve connectors with a clamping distance ≤ 116 mm in one action and for double pressings. Works anywhere, free-hand, overhead, in confined areas. Optimum weight distribution for single-hand operation. Ergonomically shaped housing with recessed grip. LED work light for illuminating the work place. Swivelling compression device for working in confined area. Compression heads quickly interchangeable, without tools. Secure spring lock seating of compression heads.

Drive

Enormous pressing force for fast and perfect jointing. Thrust force REMS Ax-Press 25 22V 20kN, thrust force REMS Ax-Press 25 L 22V 13kN. Powerful electro-hydraulic drive with automatic return (ACC), eccentric reciprocating pump with robust planetary gear. Powerful electro-hydraulic drive with powerful battery motor 21.6 V, 380 W output, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch.

Battery or mains operation

Li-Ion 22V Technology. Highly resistant Li-Ion 21.6 V battery with 1.5, 2.5, 5.0 or 9.0Ah capacity, for long service life. Light and powerful. Li-Ion 21.6 V, 1.5Ah battery for approx. 300 pressings, 2.5Ah for approx. 500 pressings, 5.0Ah for approx. 1000 pressings, 9.0Ah for approx. 1800 pressings REHAU RAUTITIAN PX Ø 16 mm with one battery charge. Graduated charging state display with coloured LED. Operating temperature range – 10 to + 60 °C. No memory effect for maximum battery power. Rapid charger Li-Ion 230V, 50–60 Hz, 70W. Rapid charger Li-Ion 230V, 50–60 Hz, 300W, for shorter charging times, as accessory. Li-Ion 230 V/21.6 V, 15A voltage supply for mains operation 230 V instead of Li-Ion battery 21.6 V, as accessory.

Expanding

Various pipe expanders and complete range of REMS expanding heads for all common pressure sleeve systems

Cordless axial press with automatic return



←ACC→

Automatic Circuit Control
with automatic circuit control
and charging status check


e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth



←ACC→

Automatic Circuit Control
with automatic circuit control
and charging status check

e.g.
AC-FIX,
BARBI,
BRASELI,
Brass & Fittings,
EUROP FLUIDES,
Fittings Estándar,
ISOLTUBEX,
PLÁSTICOS FERRO,
Velta



Tested by electro suisse ➤

German Quality Product

