

Supply format

REMS Ax-Press 25 22V ACC Basic-Pack. Cordless axial press for producing compression sleeve joints Ø 12–40 mm, 40 mm stroke, for pressing compression sleeve connections with a clamping distance ≤ 82 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 230 V or 110 V, 50–60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.
	573022

Other voltages on request.



Supply format

REMS Ax-Press 25 L 22V ACC Basic-Pack. Cordless axial press for producing compression sleeve joints Ø 12–40 mm, 40 mm stroke, for pressing compression sleeve connections with a clamping distance ≤ 116 mm. For driving REMS pressing heads. Electro-hydraulic drive with powerful battery motor 21.6 V, 380 W, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch, swivelling pressing device. LED work light. Battery Li-Ion 21.6 V, 1.5 Ah, rapid charger Li-Ion 230 V or 110 V, 50–60 Hz, 70 W. Without compression heads. In sturdy steel case.

	Art.-No.
	573023

Other voltages on request.



Accessories

Description	Art.-No.
REMS compression heads see page 202–203.	
REMS Ax-Press 25 22V ACC drive unit, without battery	573020
REMS Ax-Press 25 L 22V ACC drive unit, without battery	573021
Battery Li-Ion 21.6 V, 1.5Ah	571570
Battery Li-Ion 21.6 V, 2.5Ah	571571
Battery Li-Ion 21.6 V, 5.0Ah	571581
Battery Li-Ion 21.6 V, 9.0Ah	571583
Rapid charger Li-Ion 230 V, 50–60 Hz, 90W	571585
Rapid charger Li-Ion 230 V, 50–60 Hz, 300W	571587
Voltage supply Li-Ion 230 V/21.6 V, 15A for mains operation 230 V instead of battery Li-Ion 21.6 V.	571567
Steel case with insert	578290

