

Supply format

REMS Akku-Ex-Press Cu 22V ACC Basic-Pack. Cordless pipe expander for fast expanding of copper pipes Ø 8–42 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 1.5 Ah battery, Li-Ion 230 V, 50–60 Hz, 70 W rapid charger. Cu expander for holding the REMS Cu expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.
	575020

Other voltages on request.



Supply format

REMS Akku-Ex-Press P 22V ACC Basic-Pack. Cordless pipe expander for fast expanding of plastic and composite tubes Ø 12–40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 1.5 Ah battery, Li-Ion 230 V, 50–60 Hz, 70 W rapid charger. P expander for holding the REMS P expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.
	575021

Other voltages on request.



e.g.
aquatherm,
General Fittings,
IVT,
REHAU,
REVEL,
Seppelfricke,
TECE,
TIEMME,
Würth

Supply format

REMS Akku-Ex-Press P-CEF 22V ACC Basic-Pack. Cordless pipe expander for fast expanding of plastic tubes Ø 16–40 mm. Electro-hydraulic drive with automatic return, with powerful 21.6 V, 380 W battery motor, robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety switch. LED work light. Li-Ion 21.6 V, 1.5 Ah battery, Li-Ion 230 V, 50–60 Hz, 70 W rapid charger. P-CEF expander for holding the REMS P-CEF expander heads and suitable expander heads of other makes. Without expander heads. In sturdy steel case.

	Art.-No.
	575022

Other voltages on request.



e.g.
Brass & Fittings,
Uponor

Accessories

Description	Art.-No.
REMS Akku-Ex-Press 22V ACC drive unit, without expander, without battery	575010
Expander Cu for holding the REMS Cu expander heads and suitable expander heads of other makes for: Conical angle 18°.	575252
Expander heads Cu see page 206	
Expander P for holding the REMS P expander heads and suitable expander heads of other makes for: Conical angle 18°.	575253
Expander heads P see page 211.	
Expander P-CEF for holding the REMS P-CEF expander heads and suitable expander heads of other makes for: Conical angle 20°.	575256
Expander heads P-CEF see page 211.	
Expander tongs P-CEF (conical angle 20°), for accommodating the expander heads P-CEF 16–40 mm, 1/2–1 1/2"	150515
Battery Li-Ion 21.6 V, 1.5 Ah	571570
Battery Li-Ion 21.6 V, 2.5 Ah	571571
Battery Li-Ion 21.6 V, 5.0 Ah	571581
Battery Li-Ion 21.6 V, 9.0 Ah	571583
Rapid charger Li-Ion 230 V, 50–60 Hz, 90 W	571585
Rapid charger Li-Ion 230 V, 50–60 Hz, 300 W	571587
Voltage supply Li-Ion 230 V/21.6 V, 15A for mains operation 230 V instead of battery Li-Ion 21.6 V.	571567
Steel case with insert	578290

