

REMS Blitz

Handy self-lighting torch with turbo-flame for fast soft soldering and economic gas consumption.

Copper tubes $\leq \varnothing 35$ mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 1950°C (3500°F)

REMS Blitz – extremely fast soft soldering.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out!

Little gas consumption, only 160 g/h!

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube. Small gas bottles can be used.

Turbo-flame

Spot-flame with turbo-twisting-booster for high heating capacity and super fast soft soldering.

Supply format

REMS Blitz. Turbo soldering torch propane for soft soldering of copper tubes $\leq \varnothing 35$ mm. Piezo-electric self-lighting. Hose connector BSPP $\frac{3}{8}$ " LH. Hollow cap nut and socket BSPP $\frac{3}{8}$ " LH. In blister pack.

| | Art.-No. |
|--|----------|
| | 160010 |

Accessories

| Description | Art.-No. |
|---|----------|
| REMS soldering material see page 221. | |
| High pressure hose 3 m, BSPP $\frac{3}{8}$ " LH | 152106 |
| Pressure reducer for 5 or 11 kg gas bottles (2 bar) | 152109 |

REMS Macho

Handy self-lighting torch with turbo-flame for extremely fast brazing and soft soldering. Economic gas consumption.

Copper tubes and others $\leq \varnothing 64$ mm

Heating, annealing, burning, melting, thawing, shrinking and similar thermal procedures.

Flame temperature 2500°C

REMS Macho – super fast brazing.

Piezo-electric self-lighting

Without igniter! Pull trigger – flame comes on! Release trigger – flame goes out! Little gas consumption, only 360 g/h!

Acetylene only

Injection torch burns atmospheric oxygen. Hence only acetylene necessary.

Design

Super handy, ergonomic, with one hand only. No setting, no adjustment. Locking button for continuous operation. Only 1 universal flame tube.

Turbo-flame

Spot-flame with turbo-twisting-booster for extremely high heating capacity and super fast brazing.

Supply format

REMS Macho. Turbo soldering torch acetylene for brazing and soft soldering of copper tubes and others $\leq \varnothing 64$ mm. Piezo-electric self-lighting. Hose connector BSPP $\frac{3}{8}$ " LH. Hollow cap nut and socket $\frac{3}{8}$ " LH. In blister pack.

| | Art.-No. |
|--|----------|
| | 161010 |

Accessories

REMS soldering material see page 221.

Turbo soldering torch propane



German Quality Product



Turbo soldering torch acetylene



German Quality Product

