

REMS CamScope / CamScope S

Endoscope camera with radio signal transmission

Mobile, handy endoscope camera with radio signal transmission for low cost inspection and damage analysis of places with difficult access such as cavities, shafts, pipes etc. Documentation of photos and videos on MicroSD card. REMS CamScope S with voice recording. For battery and mains operation.

Camera head

Ø 4.5/9/16 mm

REMS CamScope – Brilliant pictures and videos of cavities, shafts and pipes. Removable controller unit. Radio signal transmission MicroSD card slot.

REMS CamScope S – with voice recording.

Design

Ultra light and handy. Hand-held unit with camera cable set only 0.3 to 0.5 kg. Can be used everywhere, free hand, over head, also in very confined spaces. Sturdy, impact-proof plastic housing with ergonomically shaped handle. On/off thumbwheel switch for continuous brightness control of the LEDs in the camera head. Power LED for indicating the operating state. Practical, removable battery holder for 4 commercially available 1.5 V, AA, LR6 batteries. Various camera cable sets can be used. Plug-screw connections for changing the camera cable sets and the push cable extensions without tools. Sturdy case for hand-held unit, camera cable set 16-1 or 9-1 or 9-2 180°/90° or 4.5-1, push cable extension, controller unit, voltage supply/charger and accessories.

Controller unit with TFT-LCD colour display

Controller unit with 3.5" colour display with state of the art TFT-LCD technology for brilliant pictures and videos, 89 mm screen diagonal, 320 × 240 pixels, removable for radio signal transmission or securely pluggable to hand-held unit for direct signal transmission by contact pins. Very light and handy: REMS CamScope only 0.14 kg, REMS CamScope S only 0.24 kg. Sturdy plastic housing, spray water protected, REMS CamScope S with rubber impact protection. Small dimensions: REMS CamScope 102 × 71 × 25 mm, REMS CamScope S 105 × 92 × 42 mm. MicroSD card slot. Photos and videos can be saved on a MicroSD card for simple documentation of the inspection result. REMS CamScope S with voice recording for easy commentary during video recording. 3x digital zoom. The date and time of the recording can be saved in the photo and video as an option. Immediate playback of saved recordings or transmission to other devices via MicroSD card. Playing of the voice recording in REMS CamScope S by external devices, e.g. PC or laptop. USB connector for direct connection to PC or laptop. Video output socket Composite-Video PAL/NTSC for connecting an external monitor. Connection for voltage supply/charger Li-Ion 100–240 V.

Cordless and mains operation

Li-Ion technology. Controller unit with integrated Li-Ion 3.7 V, 1.2 Ah battery. Light and powerful. High energy density for approx. 2 hours continuous operation. Voltage supply 100–240 V, 50–60 Hz, 9 W, for mains operation instead of battery with integrated electronic Li-Ion charger. No memory effect for maximum battery performance.

Exchangeable camera cable set Color

Camera cable set Color, consisting of colour camera Ø 4.5 mm, Ø 9 mm or Ø 16 mm, with CMOS sensor with dimmable white light LEDs for optimum setting of the brightness and fixed focus function for automatic picture focus, protected against occasional immersion in water (IP 67). Camera cable set Color 16-1 and 9-1 with 1 m flexible push cable and add-on mirror, add-on hook, add-on magnet. Camera cable set Color 9-2 180°/90° with 180° straight and 90° angled colour camera, selectable with a button, Ø 9 mm, with 2 m formable push cable. Camera cable set Color 4.5-1 with 1 m flexible push cable, ideal for inspecting small pipe bends and narrow places, e.g. odour traps, bore holes, breakthroughs. Flexible 900 mm push cable extension, connectable up to a working length of 4.5 m, as an accessory.

