

REMS SSM 160KS

Butt welding machine

Powerful, proven, easy-to-transport compact machine.
Ideal for sanitary installation, drain pipe installation,
chimney reconstruction with PVDF pipes.
For job site and workshop.

Plastic pipes and fittings

in PB, PE, PP, PVDF

\varnothing 40 – 160 mm

PE \varnothing 40 – 90 mm SDR \geq 6

PE \varnothing 40 – 110 mm SDR \geq 9

PE \varnothing 40 – 125 mm SDR \geq 11

PE \varnothing 40 – 140 mm SDR \geq 17

PE \varnothing 40 – 160 mm SDR \geq 21

REMS SSM 160KS – ideal for the pipe fitter.
Heating element according to DVS. Electronic
temperature control. High-quality PTFE coating.
Powerful facing cutter. Closed facing cutter housing.

Design

Compact, robust, job site-proven. Machine on sheet metal base weighs 101 kg.
Easy to carry.

- Base frame in aluminium cast
- Free suspension of butt welding unit REMS SSG 180 for exact alignment of the faces to be welded
- Electric facing cutter unit for plane-parallel machining of pipe ends
- Smooth sliding, roller-bearing mounting of butt welding unit and electric facing cutter unit
- Quick clamping device, also suitable for angular branches
- Pressing device, clear scale for easy reading of jointing pressure, clamping handle for pressure holding
- Machine on sheet steel base with built-in drawer for clamping and pipe rest inserts
- Suitable for use on a work bench or on the standard supplied sheet metal cabinet (= carrying case).

Heating element according to DVS

Plate-shaped, plane-parallel heating element according to DVS. Electric heater embedded in corrosion-resistant cast aluminium for indirect heat transfer.

High-quality, long-lasting PTFE coating prevents adherence of plastic remnants as well as oxidizing, and enables easy cleaning. Ideal temperature distribution and constant temperature at the complete working area. Protective cover for heating element.

Electronic temperature control

Adjustable temperature 180–290°C, preset for PE pipes. The electronic temperature control automatically controls the preset temperature within the permitted range according to DVS. Temperature control lamp and power control lamp.

Facing cutter unit

Electric facing cutter unit with special, high torque universal motor, 500 W, for plane-parallel machining of one or both pipe ends according to DVS. Fast positioning of facing cutter with proven safety switch. Closed facing cutter housing. Specially hardened and specially ground planing blades guarantee easy, vibration-free planing.

Quick clamping device, also for angular branches

Sturdy quick clamping device made of nickel-plated steel, consisting of 2 vices with 2 clamping inserts each for pipes of \varnothing 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. Also suitable for angular branches.

Pipe supports

Multiple adjustment, easy positioning of pipe supports for pipes of \varnothing 160 mm for supporting and easy axial alignment of pipes and fittings. 2 pipe support inserts each for pipes \varnothing 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm.

Supply format

REMS SSM 160KS. Butt welding machine for plastic pipes and fittings in PB, PE, PP, PVDF, PE \varnothing 40–90 mm SDR \geq 6, PE \varnothing 40–110 mm SDR \geq 9, PE \varnothing 40–125 mm SDR \geq 11, PE \varnothing 40–140 mm SDR \geq 17, PE \varnothing 40–160 mm SDR \geq 21. Butt welding unit with PTFE-coated heating element 230 V 50–60 Hz, 1200 W. Adjustable temperature 180–290°C, preset for PE pipes. Electronic temperature control. Protective cover for heating element. Electric planing device 230 V, 50–60 Hz, 500 W. Pressing device. Quick clamping device, also for angular branches, consisting of 2 vices with 2 clamping inserts each \varnothing 40, 50, 56, 63, 75, 90, 110, 125, 135, 140, 160 mm. 2 pipe rests \varnothing 160 mm with pipe rest inserts \varnothing 40, 50, 56, 63, 75, 90, 110, 125, 135, 140 mm. Sheet steel base with built-in drawer. Work key. Closed sheet metal cabinet = carrying case.

	Art.-No.
	252046

Accessories

Description	Art.-No.
Planing blade (piece)	252103



Info

