



REMS Picus S1 Basic-Pack



REMS Picus S1 Set 62

Supply format

REMS Picus S1 Basic-Pack. Electric diamond core drilling machine for core drilling in concrete, steel-reinforced concrete ≤ Ø 102 (132) mm, masonry and other materials ≤ Ø 162 mm. For dry and wet drilling, hand held or with drill stand. Drive machine with drilling crown connecting thread UNC 1¼ male, BSPP ½ female, maintenance-free gear with safety slip clutch, universal motor 230 V, 50–60 Hz, 1850 W. Multifunction electronics with soft starting, idle speed limiting, overload protection, blocking protection. Touch switch with lock. Personal protection switch (PRCD). Load speed drilling spindle 580 rpm. Water supply device with adjustable shut-off valve and quick coupling with water stop and ½" hose connection. Stabiliser. Starting aid BSPP ½ with drill Ø 8 mm, Allen key size 3. Single open-ended wrench size 32. In sturdy steel case.

	Art.-No.	
	180010	

Other voltages on request.

Supply format

REMS Picus S1 Set 62. REMS Picus S1 Basic-Pack with REMS Universal diamond core drilling crown UDKB Ø 62 mm.

	Art.-No.	
	180020	

Other voltages on request.

Supply format

REMS Picus S1 Set 62 Simplex 2. REMS Picus S1 Basic-Pack with REMS Universal diamond core drilling crowns UDKB Ø 62 mm a REMS Simplex 2 drilling stand including tools and fastening kit for masonry and concrete.

	Art.-No.	
	180031	

Other voltages on request.



REMS Picus S1 Set 62 Simplex 2

Accessories

Description	Art.-No.	
REMS Picus S1 drive unit	180000	
Steel case with inlay	180600	
REMS Universal diamond core drilling crowns, inductively soldered, resolderable, see page 264.		
REMS universal diamond core drilling crowns LS, laser welded, high temperature-resistant, see page 265.		
REMS Pull L / M, dry and wet extractors, see page 270		
Additional accessories see page 262–263.		

