

REMS roll grooving attachment

Robust, compact roll grooving attachment with oil hydraulic in-feed for pipe grooving of grooved coupling systems DN 25–300, 1–12" (page 50). Roll grooving with REMS Tornado up to DN 200, 8".



Version T

Wheel stand (accessory)



Version T

Collapsible wheel stand (Accessory)

Supply format

REMS Tornado. Threading machine for pipe threads ($\frac{1}{16}$) $\frac{1}{8}$ –2", 16–63 mm, bolt threads (6) 10–60 mm, $\frac{1}{4}$ –2". With maintenance-free gear, safety foot switch with emergency-stop, 2 automatic chucks, automatic lubrication and cooling. With tool set consisting of one universal automatic die head for all threads, also long threads, automatic opening, with automatic thread-length-stop for tapered threads. Dies for pipe threads, tapered, ISO 7-1, EN 10226 (DIN 2999, BSPT) R $\frac{1}{2}$ – $\frac{3}{4}$ " and R 1–2" right-hand, pipe cutter, inner pipe deburrer, pressing lever, adjustable height material support. Choice of 3 motors. Portable version with 3 tubular legs, with removable, large oil and chip tray. Version T with integrated, even bigger oil tray and chip tray, for workbench, stand, collapsible wheel stand or wheel stand with material shelf. In a carton.

| Description | Version | Art.-No. | |
|---------------|--|----------|--|
| 2000 | Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm. Portable, 3 legs. | 340200 | |
| 2010 | Pole-reversible capacitor, motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs. | 340201 | |
| 2020 | Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. Portable, 3 legs. | 340202 | |
| 2000 T | Universal motor 230 V or 110 V, 50–60 Hz, 1700 W. 53 rpm. For work bench, stand or wheel stand. | 340206 | |
| 2010 T | Pole-reversible capacitor motor 230 V, 50 Hz, 2100 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand. | 340207 | |
| 2020 T | Pole-reversible 3~ induction motor 400 V, 50 Hz, 2000 W. 52/26 rpm, also under full load. Extremely quiet running. For work bench, stand or wheel stand. | 340208 | |

Other voltages and NPT versions on request.

Accessories

| Description | Art.-No. | |
|---|----------|--|
| Stand | 344105 | |
| Wheel stand with material shelf | 344100 | |
| Collapsible wheel stand | 344150 | |
| Dies see page 40. | | |
| Universal automatic die head $\frac{1}{16}$–2" quick-change die head instead of changing the dies | 341000 | |
| REMS cutter wheel St $\frac{1}{8}$–4", s 8 | 341614 | |
| Thread-cutting oil see page 49. | | |
| Nipple holder see page 48. | | |
| REMS Herkules material supports, see page 102. | | |
| REMS roll grooving attachment for pipe grooving, see page 50. | 347000 | |

