

REMS RAS St

Pipe cutters

Robust quality tools for cutting pipes.
Meets high demands and long service life.

Steel pipes $\varnothing \frac{1}{8}$ –4", $\varnothing 10$ –115 mm

REMS cutter wheels for other makes see page 78.

REMS RAS St – quality pipe cutters.

Solid body in forged steel.

Robust spindle, long spindle guidance and hardened back pressure rollers provide exact alignment to the pipe and a long service life.

Ergonomic, wide handle provides a powerful in-feed of spindle.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life.

Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

Only 1 cutter wheel for pipes $\varnothing \frac{1}{8}$ –4" (10–115 mm), wall thickness $s \leq 8$ mm, suitable for both pipe cutters. Cutter wheel for pipes $\varnothing 1$ –4" to wall thickness $s \leq 12.5$ mm available as accessory.

Supply format

REMS RAS St. Pipe cutter for steel pipes. With cutter wheel. In a carton.

Description	Pipes \varnothing mm/inch	Wall thickness $s \leq$ mm	Art.-No.	
St $\frac{1}{8}$–2"	$\frac{1}{8}$ –2" 10–60	8	113000	
St $1\frac{1}{4}$–4"	$1\frac{1}{4}$ –4" 30–115	8	113100	

Accessories

Description	$s \leq$ mm	Art.-No.	
REMS cutter wheel St $1\frac{1}{8}$–4" , $s \leq 8$ for REMS RAS St $\frac{1}{8}$ –2" and St $1\frac{1}{4}$ –4"	8	341614	
REMS cutter wheel St 1–4" , $s \leq 12$ for REMS RAS St $1\frac{1}{4}$ –4"	12.5	381622	



German Quality Products



Info



REMS RAS Cu-INOX

Tubing cutters

Robust quality tools for cutting tubes.
Particularly suited for cutting stainless steel tubes.

Copper tubes, thin-walled
stainless steel tubes, thin-walled
steel, aluminium, brass tubes $\varnothing 3$ –120 mm
 $\varnothing \frac{1}{8}$ –4"

REMS cutter wheels for other makes see page 78.

REMS RAS Cu-INOX – for places with difficult access.

Small, handy, specially for use in restricted spaces.

Robust design and hardened back pressure rollers provide exact alignment to the tube and a long service life.

Large operating knob in metal for easy in-feed and cutting.

Broad, precise cutter wheel bearing on a hardened, non rotating wheel shaft guarantees a right angle cut.

Specially hardened cutter wheel in approved, tough-hard REMS die-steel quality ensures a long service life. Fast changing of cutter wheel without tools by cutter wheel axle with ball catch. Cutter wheel protected against touching the back pressure rollers by in-feed limitation.

REMS RAS Cu-INOX 3–28 S Mini with needle bearing cutter wheel and needle bearing counter-pressure rollers for very easy cutting.

Supply format

REMS RAS Cu-INOX. Tubing cutter for copper tubes, thin-walled stainless steel tubes, thin-walled steel, aluminium, brass tubes. With cutter wheel.
In blister pack.

Description	Pipes \varnothing mm/inch	Wall thickness $s \leq$ mm	Art.-No.	
Cu-INOX 3–16	3–16 $\frac{1}{8}$ – $\frac{5}{8}$ "	4	113200	
Cu-INOX 3–28 Mini	3–28 $\frac{1}{8}$ –1 $\frac{1}{8}$ "	4	113240	
Cu-INOX 3–28 S Mini, on needle bearings	3–28 $\frac{1}{8}$ –1 $\frac{1}{8}$ "	4	113241	



Info