

Supply format

REMS Cento Basic. Pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8–115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8–108 mm. For steel pipes EN 10255 (DIN 2440) DN 6–100, Ø $\frac{1}{8}$ –4", Ø 10–115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic tubes SDR 11, wall thickness $s \leq 10$ mm, Ø 10–110 mm, Ø $\frac{1}{8}$ –4", composite tubes Ø 10–110 mm. With maintenance-free gear, proven universal motor 230 V or 110 V, 50–60 Hz, 1200 W. Speed 115 rpm. Rollers in hardened precision steel pipe for pipes Ø 22–115 mm, Ø $\frac{3}{4}$ –4". Safety foot-switch. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.
	845001

Other voltages on request.



Supply format

REMS Cento RF Set. Pipe cutting machine especially for fast, right-angled cutting of welded drain pipes/down pipes made of stainless steel (EN 1124) Ø 40–110 mm. As Art. No. 845001, but with rollers made of polyamide and pipe guides Ø 75 and 110 mm. Safety foot switch. Ring spanner. With cutting wheel RF. For workbench, stand or wheel stand. In a carton.

	Art.-No.
	845003

Other voltages on request.



Accessories

Description	Art.-No.
Feed lever with spring plug for operating the drive unit on the floor (for drive units manufactured from 2014 onwards).	845218
REMS cutter wheel Cu-INOX for stainless steel pipes of pressfitting systems, copper, carbon steel	845050
REMS cutter wheel Cu especially for pipes of copper pressfitting systems	845053
REMS cutter wheel St for steel pipes, cast iron pipes (SML)	845052
REMS cutter wheel V for plastic and multilayer composite pipes, wall thickness $s \leq 10$ mm	845051
REMS cutting wheel C-SF especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055
REMS cutting wheel RF for cutting welded drain pipes/down pipes made of stainless steel (EN 1124) with REMS Cento RF.	845054
Pipe support 1 , height adjustable, for pipes Ø 40–110 mm, Ø $\frac{1}{2}$ –4", with operation of the drive unit with feed lever on the floor	845220
Hardened, precision tubular steel rollers (pack of 4)	845118
Stainless tubular steel INOX rollers (pack of 4)	845110
Polyamide roller (pack of 4)	845131
Marking device for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Akku-Cento 22V.	845530

REMS REG 10–54 E, outer/inner pipe deburrer, see page 95

REMS REG 28–108 , inner pipe deburrer for pipes Ø 28–108 mm, Ø $\frac{1}{8}$ –4", for electric drive with the REMS Cento pipe or REMS Akku-Cento 22V cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840
Stand	849315
Wheel stand	849310
REMS Jumbo , folding workbenches, see page 101.	
REMS Herkules , material supports, see page 102.	

