

### REMS pipe deburrer

Inner pipe deburrer REMS REG 28–108 for pipes Ø 28–108 mm, Ø ¾–4", for electric drive with the REMS Cento pipe cutting machine, as an accessory. Outer/inner pipe deburrer REMS REG 10–54 E for pipes Ø 10–54 mm, Ø ½–2½", for electric drive with the REMS Cento pipe cutting machine, see page 95.

### Marking device

Marking device for marking the insertion depth for fittings on pipes, as an accessory.

### Supply format

**REMS Akku-Cento 22 V Basic.** Cordless pipe cutting machine for fast, right angled, cutting of pipes with no outer burr Ø 8–115 mm. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 8–108 mm. For steel pipes EN 10255 (DIN 2440) DN 6–100, Ø ½–4", Ø 10–115 mm, cast pipes (SML) EN 877 (DIN 19522) DN 50–100, plastic tubes SDR 11, wall thickness s ≤ 10 mm, Ø 10–110 mm, Ø ½–4", composite tubes Ø 10–110 mm. With maintenance-free gear, powerful 21.6 V battery motor. Speed 84 rpm. Machine status check with overload protection, temperature monitoring, battery charging status check. Rollers in hardened precision steel pipe for pipes Ø 22–115 mm, Ø ¾–4". Safety foot-switch. Li-Ion 21.6 V, 5.0Ah battery, Li-Ion 230V, 50–60 Hz, 90 W rapid charger. Ring spanner. Without cutter wheel. For workbench, stand or wheel stand. In a carton.

	Art.-No.
	845002

Other voltages on request.

### Accessories

Description	Art.-No.
<b>Battery Li-Ion 21.6 V, 5.0Ah</b>	571581
<b>Battery Li-Ion 21.6 V, 9.0Ah</b>	571583
Rapid charger Li-Ion 230V, 50–60 Hz, 90 W	571585
Rapid charger Li-Ion 230V, 50–60 Hz, 300 W	571587
<b>Voltage supply 230V/21.6 V, 70A, for mains operation 230V instead of battery Li-Ion 21.6 V</b>	571578
Feed lever with spring plug for operating the drive unit on the floor.	845218
<b>REMS cutter wheel Cu-INOX</b> for stainless steel pipes of pressfitting systems, copper, carbon steel	845050
<b>REMS cutter wheel Cu</b> specially for pipes of copper pressfitting systems	845053
<b>REMS cutter wheel St</b> for steel pipes, cast iron pipes (SML)	845052
<b>REMS cutter wheel V</b> for plastic and multilayer composite pipes, wall thickness s ≤ 10 mm	845051
<b>REMS cutting wheel C-SF</b> especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer.	845055
<b>Pipe support 1</b> , height adjustable, for pipes Ø 40–110 mm, Ø 1½–4", with operation of the drive unit with feed lever on the floor	845220
<b>Hardened, precision tubular steel rollers (pack of 4)</b>	845118
<b>Stainless tubular steel INOX rollers (pack of 4)</b>	845110
<b>Marking device</b> for marking the insertion depth for fittings on pipes. For REMS Cento, REMS Akku-Cento 22 V.	845530

**REMS REG 10–54 E**, outer/inner pipe deburrer, see page 95

<b>REMS REG 28–108</b> , inner pipe deburrer for pipes Ø 28–108 mm, Ø ¾–4", for electric drive with the REMS Cento pipe or REMS Akku-Cento 22 V cutting machine (with REMS cutting wheel Art. No. 845050 or 845053).	113840
<b>Stand</b>	849315
<b>Wheel stand</b>	849310
<b>REMS Jumbo</b> , folding workbenches, see page 101.	
<b>REMS Herkules</b> , material supports, see page 102.	

