

## Supply format

**REMS DueCento Basic.** Pipe cutting machine for fast, right angled cutting of pipes Ø 40–225 mm, without outside burr. For pipes of the press fitting systems made from stainless steel, carbon steel, copper, Ø 54–225 mm. For steel pipes EN 10255 (DIN 2440) DN 40–150, Ø 1½–6", cast pipes (SML) EN 877 (DIN 19522) DN 50–200, plastic tubes SDR 11, wall thickness  $s \leq 21$  mm, Ø 40–225 mm, Ø 1¼–8", composite tubes Ø 40–110 mm. With maintenance-free gears, proven universal motor 110 / 230 V, 50–60 Hz, 1,200 W. Speed 115 rpm. Hardened, precision tubular steel rollers for pipes Ø 100–225 mm, Ø 4–6". Safety foot switch. Ring spanner. Without cutter wheel. 2 height adjustable pipe supports 1 for pipes Ø 100–225 mm, Ø 4–8". In a carton.

	Art.-No.
	845004

Other voltages on request.



## Accessories

Description	Art.-No.
<b>REMS cutter wheel Cu-INOX</b> for stainless steel pipes of pressfitting systems, copper, carbon steel	845050
<b>REMS cutter wheel Cu</b> specially for pipes of copper pressfitting systems	845053
<b>REMS cutter wheel St</b> for steel pipes, cast iron pipes (SML)	845052
<b>REMS cutting wheel C-SF</b> especially for pipes of the pressfitting systems and push fitting systems made from carbon steel, simultaneously produces a chamfer	845055
<b>REMS cutter wheel V, s 10</b> for plastic and multilayer composite pipes, wall thickness $s \leq 10$ mm	845051
<b>REMS cutter wheel P, s 21</b> for plastic and multilayer composite tubes, wall thickness $s \leq 21$ mm	845057
<b>Pipe support 1</b> , height adjustable for pipes Ø 100–225 mm, Ø 4–8"	845220
<b>Pipe support 2</b> , height adjustable, for pipes Ø 40–110 mm, Ø 1½–4" (roller insert required)	845230
<b>Roller insert</b> for cutting pipes Ø 40–110 mm, Ø 1½–4"	845060

