


TUBO POLIURETANO FLESSIBILE PER MOTRICE RACCORDATO
POLYURETHANE FLEXIBLE BRAIDED HOSE WITH FITTINGS

CODICE CODE	Ø mm. OUT. INS.	ROTOLI METRI ROLL METERS	CON RACCORDI WITH FITTINGS
TPUR121216F	12 x 8	12	16 x 1,5 ÷ 1/4 Femmina•Female
TPUR121216U	12 x 8	12	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling
TPUR151216F	15 x 10	12	16 x 1,5 ÷ 1/4 Femmina•Female
TPUR151216U	15 x 10	12	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling
TPUR151516F	15 x 10	15	16 x 1,5 ÷ 1/4 Femmina•Female
TPUR151516U	15 x 10	15	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling


SPIRALE IN RILSAN PER MOTRICE RACCORDATA
RILSAN SPIRAL HOSES WITH FITTINGS FOR TRACTOR

CODICE CODE	Ø mm. OUT. INS.	LUNGH. METRI LENGTH METERS	CON RACCORDI WITH FITTINGS
SR*1015RU16	10 x 8	15	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling
SR*1020RU16	10 x 8	20	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling
SR*1215RU16	12 x 10	15	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling
SR*1220RU16	12 x 10	20	16 x 1,5 ÷ 1/4 Rub. Universale•Uni Coupling

*B=Blu A=Arancio

Su richiesta raccordi 16x1,5 con altri tipi di raccordi

*B=Blue A=Orange

Upon request we can supply 16x1,5 fittings with other types of joints

TUBO NERO PA11
PA11 BLACK HOSE

CODICE CODE	Ø mm. OUT. INS.	ROTOLI ROLLS	PRESSIONE ESERCIZIO WORKING PRESSURE	PRESSIONE SCOPPIO EXPLOSION PRESSURE
TRNR0604	6 x 4	100	27	80
TRNR0806	8 x 6	100	19	57
TRNR0906	9 x 6	100	24	71
TRNR1108	11 x 8	100	20	61
TRNR1208	12 x 8	100	27	80
TRNR1209	12 x 9	100	19	57
TRNR1612	16 x 12	50	19	57



AUTOCARRO

VALVOLE CON AZIONAMENTO A LEVA 3/5 VIE 1/8
PNEUMATICALLY OPERATED SPOOL VALVES 3/5 VIE 1/8

CODICE CODE	
C58L1	1 Posizione stabile • 1 Stable position
C58L2	2 Posizioni stabili • 2 Stable positions
C58L3	3 Posizioni stabili • 3 Stable positions
C58L0	1 Posizione stabile con blocco 1 Stable position with block
EVA 3CB	Minielettropilota Mini directly operated 3/2 solenoid valve



C58L



EVA 3C-B



C58L0