

406 Extension, flexible

(right hand rotation only)
maximum torque 5 N-m.



Code	L mm	d mm	Δ g	
11 04 00 00	152	11.6	61	5

407 Universal joint

DIN 3123/ISO 3316.




Code	L mm	d mm	Δ g	
11 02 00 00	37	12.8	23	5

407QR QuickRelease universal joint

QR

with QuickRelease safety lock, patent.



Code	L mm	d mm	Δ g	
11 02 10 00	45	13	35	1

5513 Set of adaptors

NEW

No 409, 1/4" socket x 3/8" plug
No 431, 3/8" socket x 1/4" plug
No 432, 3/8" socket x 1/2" plug
No 513, 1/2" socket x 3/8" plug
No 514, 1/2" socket x 3/4" plug



Code	Δ g	
96 12 10 03	648	1

409 Adaptor

HPQ

1/4" socket x 3/8" plug (6.3 x 10),
DIN 3123/ISO 3316, HPQ® high performance steel.



Code	L mm	d mm	Δ g	
11 03 00 02	25	12.8	18	5

409M/432M/514M/3 Set adaptors, 3 pieces

1/4" socket x 3/8" plug,
3/8" socket x 1/2" plug,
1/2" socket x 3/4" plug.



Code	Δ g	
96 12 10 02	120	1

409M Adaptor

1/4" socket x 3/8" plug (6.3 x 10).



Code	L mm	ϕ mm	Δ g	
11 03 00 10	13	28	14	1

410 Adaptor

HPQ

1/4" socket x 1/2" plug (6.3 x 12.5),
HPQ® high performance steel.



Code	L mm	d mm	Δ g	
11 03 00 03	28	16.5	36	5

412 Bit holder

HPQ

○ 1/4" inside hexagon, DIN 3126/ISO 1173 D 6.3.
Internal hex drive with a collar-thrust spring.
Bits are easy to insert, lock securely in position and can be removed just as easily; even hex bits with a wide groove (Type E, DIN 3126/ISO 1173).
HPQ® high performance steel.



Code	L mm	d mm	Δ g	
11 18 00 10	25	11.6	15	5

412-1 Bit holder

HPQ

○ 1/4" inside hexagon, DIN 3126/ISO 1173 D 6.3
Outer ● 10 mm for use in tools with 10 mm
internal hex drive or internal double hexagon
(e.g. "FLEXI" double-ended flexi-joint spanners, T-handle universal joint spanners, box spanners, ratchet ring spanners etc.).
Internal hex drive with a collar-thrust spring.
Bits are easy to insert, lock securely in position and can be removed just as easily; even hex bits with a wide groove (Type E, DIN 3126/ISO 1173).
HPQ® high performance steel.



Code	Außen ●	L mm	d mm	Δ g	
11 18 00 20	10 mm	20	11.6	11	5

417/1 Locking adaptor

with hexagon key wrench
No 10760aCV 3/32".



Code	L mm	d mm	Δ g	
96 11 27 01	42	13	23	1

6.3
1/4"

DIN
3120

ISO
1174-1

3