

40aD/9/4 Socket set 1/4" ☐

in sturdy, stackable ABS plastic case,
13 pieces
Content:

- 9 sockets with bi-hexagon
 - No 40aD: sizes 3/16; 7/32; 1/4;
9/32; 5/16; 11/32; 3/8; 7/16; 1/2"
- 1 ratchet No 415
- 2 extensions
 - No 405/2 (54 mm),
 - No 405/6 (150 mm)
- 1 universal joint No 407



Code	8
9601 6302	727

40aD/12/7QR Socket set 1/4" ☐

QR
in sturdy, stackable ABS plastic case,
19 pieces
Content:

- 1 socket with hexagon No 40a:
size 1/8"
- 11 sockets with bi-hexagon
 - No 40aD: sizes 5/32; 3/16; 7/32; 1/4;
9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
- 1 ratchet No 415SG-QR N
- 3 extensions No 405/2QR (2x) (54 mm), No 405/6QR (150 mm)
- 1 universal joint No 407QR
- 1 drive handle No 400QR
- 1 bit-holder No 412



Code	8
9601 5208	917

40aD/30/7QR Socket set 1/4" ☐


QR
in sturdy, stackable ABS plastic case,
37 pieces
Content:

- 1 socket with hexagon No 40a:
size 1/8"
- 11 sockets with bi-hexagon
 - No 40aD: sizes 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
- 11 sockets with bi-hexagon, long, No 40aDL:
sizes 5/32; 3/16; 7/32; 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2; 9/16"
- 7 UNIFLEX sockets with bi-hexagon No 402a:
sizes 1/4; 9/32; 5/16; 11/32; 3/8; 7/16; 1/2"
- 1 ratchet No 415SG-QR N
- 3 extensions No 405/2QR (2x) (54 mm), No 405/6QR (150 mm)
- 1 universal joint No 407QR
- 1 drive handle No 400QR
- 1 bit-holder No 412



Code	8
9601 5205	2168

ES 1/4" + 10760CV



175 x 350 x 41 mm, 27 pieces

Code	g
9683 81 10	1035
No 40	1/4" sizes 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
No 400	1/4" 150 mm
No 404	1/4" 116 mm
No 405/2	1/4" 54 mm
No 405/6	1/4" 150 mm
No 407	1/4" 38 mm
No 412	1/4"
No 415	1/4"
No 10760CV	sizes 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10; 12 mm
8381 20 28 Empty tray	107

TCS 1/4" + 10760CV



TCS



175 x 350 x 43 mm, 27 pieces

Code	g
9683 81 76	987
No 40	1/4" sizes 5.5; 6; 7; 8; 9; 10; 11; 12; 13; 14 mm
No 400	1/4" 150 mm
No 404	1/4" 116 mm
No 405/2	1/4" 54 mm
No 405/6	1/4" 150 mm
No 407	1/4" 38 mm
No 412	1/4"
No 415	1/4"
No 10760CV	sizes 1.5; 2; 2.5; 3; 4; 5; 6; 8; 10; 12 mm

6.3
1/4"

DIN
3120

ISO
1174-1

3