

Sockets, Socket Sets

10
3/8"


DIN
3120

ISO
1174-1

46 Sockets



extra deep, metric sizes: DIN 3124/ISO 2725-1, E DIN EN 3710, E DIN EN 3709, ASME B 107.5M, American sizes: ASME B 107.1, Fed. Spec. GGG-W-641, SAE AS 954-E, HPQ® high performance steel, chrome plated.



Code	Ø mm/"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02020008	8	11.7	16.5	7	54	9	42.5	36	10	
02020010	10	14.3	16.5	9	54	20	42.5	41	10	
02020011	11	15.6	16.5	10	54	20	40.7	51	10	
02020012	12	16.9	17.5	11	54	20	40.4	57	10	
02020013	13	18	17.5	12	54	20	40.1	61	10	
02020014	14	19.4	17.5	13	60	25	45.8	75	10	
02020015	15	20.6	19	14	60	25	48.2	85	10	
02020016	16	21.7	19.5	15	60	25	47.9	81	10	
02020017	17	23	21	16	65	30	52.6	97	10	
02020018	18	24.2	22	17	65	30	52.3	121	10	
02020019	19	25.2	23	18	65	30	52	112	10	
02020208	20.8-13/16 ¹⁾	27.2	25	-	65	18	-	151	10	
02020021	21	27.7	25.5	20	65	30	51.5	137	5	
02020022	22	28.7	26.5	21	65	30	51.2	178	5	

¹⁾ with rubber insert for spark plugs

46a Sockets

Code	Ø "	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02420016	1/4	9.7	16.5	5.2	54	9	42.5	33	5	
02420020	5/16	11.7	16.5	7	54	9	42.5	35	5	
02420022	11/32	12.5	16.5	8.1	54	9	42.5	37	5	
02420024	3/8	13.7	16.5	8.4	54	20	42.5	45	5	
02420028	7/16	15.7	16.5	10	54	20	40.7	53	5	
02420032	1/2	18	17.5	11.5	54	20	40.2	64	5	
02420034	9/16	20.2	19	13.1	60	25	45.8	66	5	
02420035	19/32	20.6	19	14	60	25	48.2	84	5	
02420036	5/8	21.7	19.5	15	60	25	47.9	81	5	
02420038	11/16	23.4	21.5	16.3	65	30	52.5	114	5	
02420040	3/4	25.2	23	18	65	30	52	137	5	
02420042	13/16	27.2	25	19.4	65	30	51.6	130	5	
02420044	7/8	28.7	26.5	21	65	30	51.2	184	5	
02420046	15/16	31.5	29	22.6	65	30	50.7	195	5	
02420048	1	33	31	24.2	65	30	50.2	205	5	

5100 Rubber insert

for size 20.8 mm (No 46; 51; 51S).


Code	Δ g	g
09010001	6	5



3466 Spark plug socket



extra deep, with magnet, HPQ® high performance steel, chrome plated.




Code	Ø mm/"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02140036	16-5/8	21.8	25.5	15	85	7	72.9	180	5	

4600 Spark plug socket



extra deep, with rubber insert, HPQ® high performance steel, chrome plated.




Code	Ø mm/"	d ₁ mm	d ₂ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02120036	16-5/8	21.7	19.5	60	15	47.8	88	10	

4606 Spark plug socket



extra deep, with rubber insert, HPQ® high performance steel, chrome plated.




Code	Ø mm/"	d ₁ mm	d ₂ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02130018	18-11/16	24.2	22	65	18	52.8	132	10	

Assembly of spark plugs on motorcycles, mopeds

47 UNIFLEX sockets



SAE AS 954-E (American sizes), HPQ® high performance steel, chrome plated.



Code	Ø mm	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δ g	g	
02040010	10	14.3	17.5	9	45.5	7	12	51	1	
02040011	11	15.6	17.5	10	47.5	11	14	55	1	
02040012	12	16.9	17.5	11	48	11	14.5	54	1	
02040013	13	18.3	17.5	12	48	12	14.5	53	1	
02040014	14	19.4	17.5	13	48.5	13	14.5	55	1	
02040015	15	20.6	17.5	14	48.5	13	14.5	56	1	
02040016	16	21.8	17.5	15	51.5	14	17	58	1	
02040017	17	23	17.5	16	53.5	15	18.5	63	1	
02040018	18	24.2	17.5	17	54.5	16	18.5	61	1	
02040019	19	25.5	17.5	18	57	16	21	68	1	