


47a UNIFLEX sockets

Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
02 44 00 20	5/16	11.7	17.5	7	45.5	7	12.5	50	1
02 44 00 24	3/8	13.7	17.5	8.5	45.5	7	12	50	1
02 44 00 28	7/16	15.8	17.5	10	47.5	11	14	50	1
02 44 00 32	1/2	18.3	17.5	11.5	47.5	11.5	14	57	1
02 44 00 34	9/16	19.7	17.5	13.1	48.5	13	14.5	55	1
02 44 00 36	5/8	21.6	17.5	15	51.5	14	17	59	1
02 44 00 38	11/16	23.5	17.5	16.3	53.5	16	18.5	58	1
02 44 00 40	3/4	25.5	17.5	18	57	16	21	67	1

45TX Sockets

HPQ

for external TORX® screws, HPQ® high performance steel, chrome plated.



Code	size	mm	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
02 27 00 05	E5	4.7	7	16.5	2.8	28	5	16.5	23	10
02 27 00 06	E6	5.7	8	16.5	3.6	28	5.5	16.5	23	10
02 27 00 07	E7	6.2	9	16.5	3.8	28	6.5	16.5	24	10
02 27 00 08	E8	7.5	10.5	16.5	4.3	28	7	16.5	22	10
02 27 00 10	E10	9.4	13	16.5	5.6	28	8	16.5	27	10
02 27 00 12	E12	11.1	14.9	16.5	7.2	28	9.5	16.5	28	10
02 27 00 14	E14	12.9	16.5	17.3	8	28	10	16.5	34	10

45TX/7 Set: Sockets

HPQ

for external TORX® screws.
Content: E5; E6; E7; E8; E10; E12; E14



Code	g	
96 02 27 02	219	1

packed in carton

47TX UNIFLEX sockets

for external TORX® screws, Chrome Alloy Steel, chrome plated.




Code	size	mm	d ₁ mm	d ₂ mm	L mm	Δg	
02 07 00 08	E8	7.5	11.5	19	43	56	1
02 07 00 10	E10	9.4	13.8	19	44	61	1
02 07 00 12	E12	11.1	16	19	46	66	1
02 07 00 14	E14	12.9	17.8	19	48	75	1

45aSP Sockets spline-drive

HPQ

MS-33787, MIL-W-8982, HPQ® high performance steel, chrome plated.




Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
02 01 10 12	12	3/8	13.7	16.5	8.6	26.5	9	15	24	1
02 01 10 14	14	7/16	16	17.3	10.4	28	11	14.5	37	1
02 01 10 16	16	1/2	18	18.3	12.2	28	11.5	14	28	1

45aPSP Socket spline-drive

HPQ

MS-33787, MIL-W-8982, for disassembling jet engines, series CFM 56, HPQ® high performance steel, gunmetal finish.




Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
22 41 00 28	14	7/16	18.8	18.8	10.4	28	11	14.5	36	10

46aSP Sockets spline-drive

HPQ

extra deep bolt clearance, MS-33787, MIL-W-8982, HPQ® high performance steel, chrome plated.




Code	Spline size	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
02 02 10 12	12	3/8	13.7	16.5	8.6	54	9	42.5	52	1
02 02 10 14	14	7/16	16	17.3	10.4	54	11	42.5	63	1

45aP Socket

AS DRIVE

HPQ

ASME B 107.1, Fed. Spec. GGG-W-641, SAE AS 954-E (test loads), for disassembling jet engines, series CFM 56, HPQ® high performance steel, gunmetal finish.



Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg	
02 43 00 20	5/16	11.9	16.5	8.1	25	7	13.5	19	10

10
3/8"

DIN
3120

ISO
1174-1

3