

540a HD CROW-FOOT spanners Heavy Duty

for particularly high loadings, e.g. stainless steel screw fittings.
Full use of jaws in conjunction with standard ratchets.
Caution! Modified settings on torque wrench (refer to note on page 187),
chrome plated. Supplied without ratchet.



Code	⌀"	⌀"	L mm	b mm	a mm	S mm	Δ g	
02 50 10 24 NEW	3/8	3/8	39	26	11	24	58	1
02 50 10 28 NEW	7/16	3/8	40	26	11	25	58	1
02 50 10 32 NEW	1/2	3/8	42	30	11	25.8	67	1
02 50 10 34	9/16	3/8	43.4	32	11	26.8	52	1
02 50 10 36	5/8	3/8	45	34.8	11	27.7	58	1
02 50 10 38	11/16	3/8	47.2	38	11	28.6	69	1
02 50 10 40 NEW	3/4	3/8	49	41	11	29.6	96	1
02 50 10 42	13/16	3/8	51	46.4	11	30.5	113	1
02 50 10 44	7/8	3/8	52	48	11	31.3	99	1
02 50 10 46	15/16	3/8	54	51.2	11	32.3	129	1
02 50 10 48	1	3/8	56	53.4	11	33.2	133	1
02 50 10 50	1 1/16	3/8	57	53.8	11	34.1	124	1
02 50 10 52	1 1/8	3/8	59	53.8	11	35	128	1
02 50 10 54 NEW	1 3/16	3/8	60	56	11	35.9	148	1
02 50 10 56	1 1/4	3/8	62	60	11	36.8	153	1
02 50 10 58 NEW	1 5/16	3/8	63	56	11	27.9	160	1
02 50 10 60 NEW	1 3/8	3/8	65	62	11	38.7	180	1
02 50 10 62	1 7/16	3/8	66.5	66	11	39.6	172	1
03 50 10 64	1 1/2	1/2	76	70	16	45	310	1
03 50 10 69	1 13/16	1/2	85	84	16	49.6	400	1
03 50 10 72	2	1/2	89	90	16	52.3	451	1
03 50 10 74	2 1/8	1/2	91.5	92.8	16	54.2	460	1
03 50 10 75	2 3/16	1/2	93	96	16	55.1	480	1
03 50 10 76	2 1/4	1/2	95	99	16	56	500	1



1225 Special extension

3/8" ■, offset




Code	L mm	d mm	Δ g	
12 25 00 01	150	17	128	5

447 Adaptor



Caution! Modified settings on torque wrench (refer to note on page 187),
American sizes: SAE AS 954-E, HPQ® high performance steel, gunmetal
finish.



Code	⌀ mm	⌀ "	d ₁ mm	d ₂ mm	h ₁ mm	h ₂ mm	S mm	Δ g	
02 18 10 07	7	3/8	11.5	19	6	11	50.8	30	1
02 18 10 08	8	3/8	12.4	19	6	11	50.8	30	1
02 18 10 09	9	3/8	14	19	8	11	50.8	40	1
02 18 10 10	10	3/8	15.6	19	8	11	50.8	40	1
02 18 10 13	13	3/8	19.3	19	9.2	11	50.8	55	1


447a Adaptor

Code	⌀ mm	⌀ "	d ₁ mm	d ₂ mm	h ₁ mm	h ₂ mm	S mm	Δ g	
02 47 00 16	1/4	3/8	10.4	19	6	11	50.8	27	1
02 47 00 20	5/16	3/8	12.4	19	6	11	50.8	29	1
02 47 00 24	3/8	3/8	14.9	19	8	11	50.8	41	1
02 47 00 28	7/16	3/8	17	19	8	11	50.8	40	1
02 47 00 32	1/2	3/8	19	19	9.2	11	50.8	56	1
02 47 00 34	9/16	3/8	21	19	9.2	11	50.8	61	1
02 47 00 36	5/8	3/8	23	19	12	11	50.8	73	1

447aSP Spline-Drive-Adapter



Caution! Modified settings on torque wrench (refer to note on page 187),
MS-33787, MIL-W-8982, HPQ® high performance steel, gunmetal finish.



Code	Spline size	⌀ "	⌀ mm	d ₁ mm	d ₂ mm	h ₁ mm	h ₂ mm	S mm	Δ g	
02 48 00 14	7	3/8	7/32	9.4	19	6	11	50.8	28	1
02 48 00 16	8	3/8	1/4	10.4	19	6	11	50.8	27	1
02 48 00 18	9	3/8	9/32	11.5	19	6	11	50.8	29	1
02 48 00 20	10	3/8	5/16	12.4	19	6	11	50.8	29	1
02 48 00 24	12	3/8	3/8	14.9	19	8	11	50.8	38	1
02 48 00 28	14	3/8	7/16	17	19	9.2	11	50.8	39	1
02 48 00 32	16	3/8	1/2	19	19	9.2	11	50.8	59	1
02 48 00 34	18	3/8	9/16	21	19	9.2	11	50.8	55	1
02 48 00 36	20	3/8	5/8	23	19	12	11	50.8	74	1

10
3/8"

12.5
1/2"

DIN
3120

ISO
1174-1

3