

1427 BITS

for inside TORX® screws.



Code	size	outside mm	"	L mm	g	
08 13 10 25	T 25	C 6.3	1/4	65	18	1

For BMW series 3 and 5
outside DIN 3126/ISO 1173

1436 IP- 1446 IP BITS

for inside TORX PLUS® screws.



Code	No	outside mm	"	L mm	g	
08 16 20 06	1436 IP 6	C 6.3	1/4	25	5	10
08 16 20 07	1437 IP 7	C 6.3	1/4	25	4	10
08 16 20 08	1438 IP 8	C 6.3	1/4	25	4	10
08 16 20 09	1439 IP 9	C 6.3	1/4	25	4	10
08 16 20 10	1440 IP 10	C 6.3	1/4	25	4	10
08 16 20 15	1441 IP 15	C 6.3	1/4	25	5	10
08 16 20 20	1442 IP 20	C 6.3	1/4	25	5	10
08 16 20 25	1443 IP 25	C 6.3	1/4	25	5	10
08 16 20 27	1444 IP 27	C 6.3	1/4	25	5	10
08 16 20 30	1445 IP 30	C 6.3	1/4	25	6	10
08 16 20 40	1446 IP 40	C 6.3	1/4	25	6	10

1440 TPI- 1446 TPI 5-star BITS

with hollow point,
for female 5-star screws with
a centring pin.



Code	No	outside mm	"	L mm	g	
08 16 10 10	1440 TPI 10	C 6.3	1/4	26	6	5
08 16 10 15	1441 TPI 15	C 6.3	1/4	26	5	5
08 16 10 20	1442 TPI 20	C 6.3	1/4	26	5	5
08 16 10 25	1443 TPI 25	C 6.3	1/4	26	5	5
08 16 10 27	1444 TPI 27	C 6.3	1/4	26	5	5
08 16 10 30	1445 TPI 30	C 6.3	1/4	26	5	5
08 16 10 40	1446 TPI 40	C 6.3	1/4	26	7	5

outside DIN 3126/ISO 1173

1204/8 5-star BITS set

Storage facility for BITS screwdriver
inserts.

Content:

- 1 bit-holder No 412
- 7 BITS screwdriver inserts for
female 5-star screws with centring pin,
sizes TPI 10, 15, 20, 25, 27, 30, 40.

For generators, motor management units,
airflow sensors, door trim, immobilisers
and injection pumps
(e.g. Ford, Mercedes-Benz cars & HGVs,
Rover, Volvo, VW/Audi).



Code	g	
96 08 11 13	87	1

1300-1304 BITS

DIN 7426/ISO 3109,
for socket head screws, extra hard.



Code	No	mm	outside mm	"	L mm	g	
08 09 00 03	1300	3	C 6.3	1/4	25	4	10
08 09 00 04	1301	4	C 6.3	1/4	25	5	10
08 09 00 05	1302	5	C 6.3	1/4	25	6	10
08 09 00 06	1303	6	C 6.3	1/4	25	6	10
08 09 00 08	1304	8	C 6.3	1/4	30	11	10

outside DIN 3126/ISO 1173

1299 BITS

for inside hexagon screws,
for operating the adjusting
screws on torque wrenches
No 720, 721, 730 and 730N.



Code	mm	outside mm	"	L mm	g	
08 09 00 02	2	C 6.3	1/4	34	4	10

outside DIN 3126/ISO 1173

13008 BITS

for TRI-WING® screws.



Code	TRI- WING®	outside mm	"	L mm	g	
08 25 00 00	0	C 6.3	1/4	25	5	10
08 25 00 01	1	C 6.3	1/4	25	5	10
08 25 00 02	2	C 6.3	1/4	25	5	10
08 25 00 03	3	C 6.3	1/4	25	5	10
08 25 00 04	4	C 6.3	1/4	25	5	10
08 25 00 05	5	C 6.3	1/4	25	5	10
08 25 00 06	6	C 6.3	1/4	25	8	10

outside DIN 3126/ISO 1173

13010 BITS

for TORQ-SET® screws.



Code	TORQ- SET®	outside mm	"	L mm	g	
08 26 00 00	0	C 6.3	1/4	25	5	10
08 26 00 01	1	C 6.3	1/4	25	5	10
08 26 00 02	2	C 6.3	1/4	25	5	10
08 26 00 03	3	C 6.3	1/4	25	5	10
08 26 00 04	4	C 6.3	1/4	25	5	10
08 26 00 05	5	C 6.3	1/4	25	5	10
08 26 00 06	6	C 6.3	1/4	25	5	10
08 26 00 08	8	C 6.3	1/4	25	5	10
08 26 00 10	10	C 6.3	1/4	25	5	10
08 26 00 16	1/4 A	C 8	5/16	32	11	10
08 26 00 20	5/16 A	C 8	5/16	32	11	10
08 26 00 24	3/8 A	C 8	5/16	32	11	10

outside DIN 3126/ISO 1173