


714R

MANOSKOP® tightening angle torque wrenches with reversible ratchet insert tool


714R/2



714R/20



714R/80



Code	size				mm	"	g	g with box
96 50 1001	1	1-10 N·m	0,7-7,5 ft·lb	9-90 in·lb	9x12	1/4	432	857
96 50 1002	2	2-20 N·m	1,5-15 ft·lb	18-180 in·lb	9x12	1/4	442	867
96 50 1004	4	4-40 N·m	3-30 ft·lb	36-360 in·lb	9x12	1/4	482	907
96 50 1006	6	6-60 N·m	4,5-45 ft·lb	54-540 in·lb	9x12	3/8	965	1390
96 50 1010	10	10-100 N·m	7,4-75 ft·lb	90-900 in·lb	9x12	1/2	1232	1657
96 50 1020	20	20-200 N·m	15-150 ft·lb	180-1800 in·lb	14x18	1/2	1663	2198
96 50 1040	40	40-400 N·m	30-300 ft·lb	360-3600 in·lb	14x18	3/4	2275	5665
96 50 1065	65	65-650 N·m	48-480 ft·lb	580-5800 in·lb	22x28	3/4	5137	9000
96 50 1080	80	80-800 N·m	60-600 ft·lb	720-7200 in·lb	22x28	3/4	6487	12300
96 50 1100	100	100-1000 N·m	74-750 ft·lb	900-9000 in·lb	22x28	3/4	6905	12500

7732-2

SENSOMASTER Live software

- Record torqueing operations with the MANOSKOP® 714, SENSOTORK® 713R (from firmware 4.x) and SENSOTORK® 701.
- Representation of torque over time, angle over time, torque over angle.
- Representation of several curves simultaneously.
- Data export for further processing.
- The software is for a single-seat licence.
- Torque wrenches 714/1 ... /100 must have firmware version 02.01.02.



Code	g
96 58 52 35	111

7195-2

Li-ion battery for No 714

M charge voltage 4.2 V, capacity 2600 mAh
Warning - hazardous goods: Rechargeable cell block Li-ion for torque wrenches in accordance with UN 3480, Class 9



Code	g
54 10 11 95	100

7160

Charging dock for Li-ion battery No 7195-2

including charger
Input: 100 V-240 V AC ,
Output: 4.2 V DC,
Charge duration: 4 hrs.
with interchangeable socket adaptors.



Code	g
54 10 00 60	200

7762

Docking station for No 714

stationary base for securely connecting angle-controlled torque wrench No 714 to a PC via a USB port.



Code	g
52 11 00 62	421



7762-1

Rest for docking station No 7762

for securely supporting long angle-controlled torque wrenches No 714 from size 6 up.



Code	g
52 11 01 62	520

7761/3

Interface adaptor set

required for automated calibration and adjustment of angle-controlled torque wrench No 714 using calibrating and adjusting units perfectControl No 7794-2 and 7794-3.

Contents
No 7761 interface adaptor
No 7752 spiral cable
No 7760 mains adaptor



Code	g
96 52 11 61	446