

## Accessories

### 7301/7302 Plastic case, empty

for safe storage and transport of torque wrenches (please order inlays separately). Supplied without torque wrench.



Code	No	for torque wrenches	L mm	$\Delta\Delta$ g
<b>81 37 00 02</b>	<b>7301</b>	712R/6; 713R/6; 714/1-10; 721/5-20 Quick; 730/5-20 Quick; 730/5-20 Fix; 730N/5-20; 730D/10	550	425
<b>81 37 00 03</b>	<b>7302</b>	713R/20; 714/20; 721/30 Quick; 730/40 Quick; 730/40 Fix; 730N/40; 730D/20	680	535

### 7303/7304 Inlays for plastic case

Code	No	for torque wrenches	$\Delta\Delta$ g
<b>83 07 10 04</b>	<b>7303</b>	712R/6; 713R/6; 721/5-20 Quick; 730/5-20 Quick; 730/5-20 Fix; 730N/5-20; 730D/10	88
<b>83 07 10 02</b>	<b>7304</b>	713R/20; 721/30 Quick; 730/40 Quick; 730/40 Fix; 730N/40; 730D/20	113

### TWBE 65-100 Textile bags for larger torque wrenches


For safe storage and transport of large torque wrenches



Code	No	for torque wrenches	$\Delta\Delta$ g
<b>81 23 11 00</b>	<b>TWBE 65</b>	714/65; 730/65 Quick; 730II/65 Quick; 730N/65; 730NII/65; 730/65 Fix; 730II/65 Fix; 730D/65; 730DII/65	670
<b>81 23 11 01</b>	<b>TWBE 80</b>	714/80; 71/80; 71aR/80; 720Nf/80; 721Nf/80; 730/80; 730D/80	714
<b>81 23 11 02</b>	<b>TWBE 100</b>	714/100; 730N/80; 730/80 Fix; 730N/100; 730D/100	760
<b>81 23 11 03</b>	<b>TWBE 721NF/100</b>	721Nf/100	850

### 7380N/7385N Torque angle gauges

for angle controlled bolt/screw tightening, with static read-off point. Read-off possible from any angle thanks to a pair of angled scales. Removable magnet for attaching sockets with  $1/2$ " internal square drive. For use in conjunction with tightening tools such as Service MANOSKOP® No 730N. Since this tightening method requires a pre-determined snug torque to be applied, it is essential to choose a torque wrench covering both snug torque as well as maximum torque required to reach the recommended tightening angle. Whether  $1/2$ " or  $3/4$ " sq.dr. Torque Angle Gauge is used depends upon the square drive of the appropriate torque wrench employed.



Code	No	$\odot$ "	$\blacksquare$ "	mm	mm	mm	$\Delta\Delta$ g
<b>54 01 00 01</b>	<b>7380N</b>	$1/2$	$1/2$	$\pm 360^\circ$	$2^\circ$	78	43
<b>54 01 00 02</b>	<b>7385N</b>	$3/4$	$3/4$	$\pm 360^\circ$	$2^\circ$	78	76

### 7161 QuickRelease safety lock

prevents insert tools being swapped. The system is locked in place on the head of the torque wrench by means of a safety screw. Once the protection system has been fitted, it is possible to attach an insert tool but not to remove it because the QuickRelease unlock button itself is locked. After the safety screw has been removed, the torque wrench reverts to being a standard, versatile tool.



The safety screw can be fitted and removed using a TORX® screwdriver with a central bore in the tip (No 4656, Size T20, Code 46 56 00 20) or a BITS screwdriver insert with a central bore in the tip (No 1442, Size T20, Code 08 16 00 20).

Code	size	for torque wrenches	$\Delta\Delta$ g
<b>54 10 00 70</b>	<b>1</b>	714/1-4	4
<b>54 10 00 71</b>	<b>2</b>	712R/6; 713R/6; 714/6-10; 730/10 Quick; 730/10 Fix; 730N/10; 730D/10	5
<b>54 10 00 72</b>	<b>3</b>	713R/20-40; 714/20-40; 730/12-40 Quick; 730/12-40 Fix; 730N/12-40; 730D/20-40	11
<b>54 10 00 73</b>	<b>4</b>	730/5 Quick; 730/5 Fix; 730N/5	2
<b>54 10 00 74</b>	<b>5</b>	714/65-100; 730II/65; 730II/65 Quick; 730II/65 Fix; 730/80-100 Fix; 730NII/65; 730N/80-100; 730DII/65; 730D/80-100	15

for other torque wrenches on request.

### 7396 LED lighting

for torque wrenches

If light is poor, simply attach this LED lamp to illuminate the work site.

Included in the delivery is a 1.5 V micro battery.

Supplied without torque wrench.



Code	No	for torque wrenches	$\Delta\Delta$ g
<b>54 01 00 04</b>		712R/6; 713R/6-40; 714/6-40; 721/5-30 Quick; 730/5-40 Quick; 730/5-40 Fix; 730N/5-40; 730D/10-40	51

### 1299 BIT

for inside hexagon screws, for operating the adjusting screws on torque wrenches No 720, 721, 730 and 730N.



Code	mm	outside	"	L mm	$\Delta\Delta$ g	$\Delta\Delta$ g
<b>08 09 00 02</b>	<b>2</b>	C 6.3	$1/4$	34	4	10

outside  $\bullet$  DIN 3126/ISO 1173