

Insert/shell tools for torque wrenches

Output square drive in accordance with DIN 3120


Long-term loading of the input and output square drive is in accordance with DIN EN ISO 6789.

This limit must not be exceeded if larger torque wrenches and tool holders are used.

725QR QuickRelease ratchet insert tools

QR

reversible, with QuickRelease safety lock, size 4: 22 teeth, sizes 5 and 10: 30 teeth




Code	size	"	mm	b mm	h mm	S mm	max. N·m	$\Delta \nabla$ g
58 25 3004	4	1/4	9x12	22	13.8	17.5	40	60
58 25 3005	5	3/8	9x12	29	18	28*	100	130
58 25 3010	10	1/2	9x12	29	18	28*	100	141

* Caution! Modified settings on torque wrench (refer to note on page 187).

725B Bit ratchet insert tool

reversible, with inside hexagon, 1/4" or 5/16", DIN 3126/ISO 1173 D 6.3 or D8, for direct acceptance of bits 1/4" or 5/16" outside hexagon C 6.3 (size 4: 22 teeth, size 5: 30 teeth). Internal hex drive with a collar-thrust spring. Bits are easy to insert, lock securely in position and can be removed just as easily; even hex bits with a wide groove (Type E, DIN 3126/ISO 1173). Supplied without bits.




Code	size	inside "	mm	b mm	h mm	S mm	$\Delta \nabla$ g
58 25 5004	4	1/4	9x12	22	13.6	17.5	54
58 25 5005	5	5/16	9x12	29	17.9	28*	117

* Caution! Modified settings on torque wrench (refer to note on page 187).

725/4 Ratchet insert tool


reversible, 22 teeth.



Code	"	mm	b mm	h mm	S mm	max. N·m	$\Delta \nabla$ g
58 25 4004	1/4	9x12	22	13.8	17.5	40	62


735 Ratchet insert tools, fine tooth

reversible, 60 teeth.



Code	size	"	mm	b mm	h mm	S mm	max. N·m	$\Delta \nabla$ g
58 25 0005	5	3/8	9x12	33	24	17.5	100	155
58 25 0010	10	1/2	9x12	33	24	17.5	100	147


734 Square drive insert tools



Code	size	"	mm	b mm	h mm	S mm	max. N·m	$\Delta \nabla$ g
58 24 0004	4	1/4	9x12	20	14	17.5	40	71
58 24 0005	5	3/8	9x12	20	14	17.5	80	76
58 24 0010	10	1/2	9x12	20	14	17.5	100	82

734F Square drive insert tools

with permanently attached, captive square drive.




Code	size	"	mm	b mm	h mm	max. N·m	$\Delta \nabla$ g
58 24 1004	4	1/4	9x12	22	14	40	72
58 24 1005	5	3/8	9x12	22	14	80	75

725L/5 Ratchet insert tool

reversible, 30 teeth.

Caution! Modified settings on torque wrench (refer to note on p. 187). This ratchet insert tool has the same extension length as ring insert tool No 732G/10 (see p. 211) and square drive insert tool No 734L/5 (see p. 210).



Code	"	mm	b mm	h mm	max. N·m	$\Delta \nabla$ g
58 15 1005	3/8	9x12	27.5	19.6	100	164