


## Insert/shell tools

### 735/65 Ratchet insert tool, fine tooth


reversible, 60 teeth, load capacity up to 650 N-m, for size 65 torque wrenches.



| Code        | "   | mm    | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|-----|-------|---------|---------|---------|---------------|
| 58 25 10 65 | 3/4 | 22x28 | 61      | 35      | 55      | 1100          |


### 735/100 Ratchet insert tool

with push through square drive, 30 teeth.




| Code        | "   | mm    | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|-----|-------|---------|---------|---------|---------------|
| 58 25 01 00 | 3/4 | 22x28 | 76      | 42      | 55      | 1893          |

### 734/100 Square drive insert tool




| Code        | "   | mm    | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|-----|-------|---------|---------|---------|---------------|
| 58 24 01 00 | 3/4 | 22x28 | 43      | 42      | 55      | 1171          |

### 731/100 Open ended insert tools



| Code        | mm | mm    | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|----|-------|---------|---------|---------|---------------|
| 58 21 10 24 | 24 | 22x28 | 50      | 13      | 55      | 628           |
| 58 21 10 27 | 27 | 22x28 | 56      | 14      | 55      | 648           |
| 58 21 10 30 | 30 | 22x28 | 63      | 15      | 55      | 695           |
| 58 21 10 32 | 32 | 22x28 | 67      | 15      | 55      | 713           |
| 58 21 10 34 | 34 | 22x28 | 72      | 15      | 55      | 739           |
| 58 21 10 36 | 36 | 22x28 | 74      | 15      | 55      | 727           |
| 58 21 10 41 | 41 | 22x28 | 84      | 16      | 55      | 902           |
| 58 21 10 46 | 46 | 22x28 | 94      | 17      | 55      | 952           |
| 58 21 10 50 | 50 | 22x28 | 104     | 18      | 55      | 1074          |
| 58 21 10 55 | 55 | 22x28 | 114     | 19      | 55      | 1174          |
| 58 21 10 60 | 60 | 22x28 | 124     | 20      | 55      | 1230          |


### 732/100 Ring insert tools



| Code        | mm | mm    | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|----|-------|---------|---------|---------|---------------|
| 58 22 10 24 | 24 | 22x28 | 43      | 15      | 55      | 629           |
| 58 22 10 27 | 27 | 22x28 | 43      | 15      | 55      | 619           |
| 58 22 10 30 | 30 | 22x28 | 46      | 16      | 55      | 632           |
| 58 22 10 32 | 32 | 22x28 | 49      | 16      | 55      | 625           |
| 58 22 10 34 | 34 | 22x28 | 52      | 17      | 55      | 638           |
| 58 22 10 36 | 36 | 22x28 | 54      | 17      | 55      | 631           |
| 58 22 10 41 | 41 | 22x28 | 61      | 18      | 55      | 642           |
| 58 22 10 46 | 46 | 22x28 | 66      | 19      | 55      | 640           |
| 58 22 10 50 | 50 | 22x28 | 75      | 20      | 55      | 713           |
| 58 22 10 55 | 55 | 22x28 | 84      | 21      | 55      | 791           |
| 58 22 10 60 | 60 | 22x28 | 93      | 22      | 55      | 885           |

### 737/100 Blank end insert tool

gunmetal finish. To prevent damage from excessive temperatures, the locking pin, spring and washer are not fitted until the welding work has been completed. Instructions are supplied.



| Code        | Welding surface<br>h x b in mm | mm    | H<br>mm | L<br>mm | $\Delta$<br>g |
|-------------|--------------------------------|-------|---------|---------|---------------|
| 58 27 01 00 | 15 x 50                        | 22x28 | 32      | 24      | 521           |

### 7370/100 Adaptor


for using shell tools with an internal square drive of 24.5 x 28 mm on torque wrenches with an internal square drive of 22 x 28 mm. Caution! Modified settings on torque wrench (refer to note on p. 187).



| Code        | mm    | mm      | L<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|-------|---------|---------|---------|---------------|
| 58 29 11 00 | 22x28 | 24,5x28 | 85      | 100     | 563           |

### 735/80 Ratchet shell tool

with push through square drive, 30 teeth.



| Code        | "   | mm      | b<br>mm | h<br>mm | S<br>mm | $\Delta$<br>g |
|-------------|-----|---------|---------|---------|---------|---------------|
| 58 25 00 80 | 3/4 | 24,5x28 | 76      | 43      | 95      | 2000          |