

Accessories for workshop torque tester and calibration systems

7750 Display unit

registered design, for displaying the actual torque as measured.

Units of measurement: N·m, ft·lb, in·lb.

Modes of operation: track, peak hold, first peak (only with manual operation), additional display of actual torque applied with clicking torque wrenches. Swivels to any desired position thanks to universal ball-joint.



| Code | L m | Δg |
|--------------------|--------|-----|
| 52 10 00 50 | 1.5 | 182 |

7759-4 USB adaptor, jack cable and software Torkmaster

Link between perfectControl or transducer and PC. For adjusting and calibrating torque wrenches and torque screwdrivers.

Produces calibration certificates in accordance with DIN EN ISO 6789, which can be printed out or saved as PDF files.

- as found / as left calibrations can be documented.
- graphical representation of the torque progression
- user management
- 17 languages
- equipment testing system

System requirements:

- PC
- Microsoft Windows XP SP3 or later operating system
- USB connection



| Code | L m | Δg |
|--------------------|--------|-----|
| 96 58 36 29 | 1.5 | 137 |

7751 Jack cable

Connection between transducers 7721-7724 and USB adaptor or display unit, with jacks at both ends, 90° angled.



| Code | L m | Δg |
|--------------------|--------|----|
| 52 11 00 51 | 1.5 | 50 |

7752 Spiral cable

Connection between transducer and display unit or USB adaptor, with jacks at both ends, 90° angled.



| Code | L M mm | Δg |
|--------------------|-----------|----|
| 52 11 00 52 | 500 | 35 |

7751-1 Cable for No 7728

for connecting laboratory transducers 7728 to a USB hub or display unit, with jack plug, 90° angled, and self-locking precision plug..



| Code | L m | Δg |
|--------------------|--------|----|
| 52 11 00 54 | 1.5 | 50 |

7751-2 Spiral cable for No 7728

for connecting laboratory transducers 7728 to a USB hub or display unit, with jack plug, 90° angled, and self-locking precision plug.



| Code | L M mm | Δg |
|--------------------|-----------|----|
| 52 11 00 57 | 500 | 50 |

7760 Mains adaptor

Input:
110 V-230 V AC ,
Output: 9 V DC,
with interchangeable socket adaptors.



| Code | Volt | Δg |
|--------------------|---------|-----|
| 52 11 00 56 | 110-230 | 385 |

7761 Interface adaptor

Input:
110 V-230 V AC ,
Output: 9 V DC,
with interchangeable socket adaptors.



| Code | Δg |
|--------------------|----|
| 52 11 00 61 | 26 |

7761/3 Interface adaptor set

Contents
No 7761 interface adaptor
No 7752 spiral cable
No 7760 mains adaptor



| Code | Δg |
|--------------------|-----|
| 96 52 11 61 | 446 |