


Screwdrivers

4632SK

⊕ Cross-head screwdrivers DRALL⁺

with impact cap and hexagonal shank, Phillips-Recess®, DIN ISO 8764-1, -2, ISO 8764-1, -2, Chrome Alloy Steel, chrome plated, black tips.




Code	PH size	L ₁ mm	L ₂ mm	△△ g	📦
46 32 31 01	1	85	190	58	10
46 32 31 02	2	100	215	130	10
46 32 31 03	3	150	275	194	5

4640

⊕ Cross-head screwdrivers DRALL⁺

POZIDRIV/SUPADRIV®, DIN ISO 8764-1, -2, ISO 8764-1, -2, Chrome Alloy Steel, chrome plated, black tips.



Code	PZ size	L ₁ mm	L ₂ mm	△△ g	📦
46 40 30 00	0	60	145	35	10
46 40 30 01	1	80	185	44	10
46 40 30 02	2	100	215	89	10
46 40 30 03	3	150	275	145	5

4636

⊕ TORQ-SET® screwdrivers DRALL⁺

TORQ-SET®, hexagonal blade, chrome plated, black tips.



Code	No	L ₁ mm	L ₂ mm	Außen " "	△△ g	📦
46 36 30 02	2	100	215	1/4	92	5
46 36 30 04	4	100	215	1/4	93	5
46 36 30 06	6	100	215	1/4	92	5
46 36 30 08	8	100	215	1/4	93	5
46 36 30 10	10	100	215	1/4	93	5
46 36 30 16	1/4	150	265	5/16	138	5

4650

⊕ TORX® screwdrivers DRALL⁺

for inside TORX® screws, Chrome Alloy Steel, chrome plated, black tips.



Code	size	mm	L ₁ mm	L ₂ mm	△△ g	📦
46 50 30 05	T5	1.4	60	145	30	5
46 50 30 06	T6	1.6	60	145	35	5
46 50 30 07	T7	2.0	60	145	35	5
46 50 30 08	T8	2.3	60	145	33	5
46 50 30 09	T9	2.5	60	145	35	5
46 50 30 10	T10	2.7	80	165	40	5
46 50 30 15	T15	3.3	80	165	38	5
46 50 30 20	T20	3.8	100	205	46	5
46 50 30 25	T25	4.4	100	205	50	5
46 50 30 27	T27	5.0	115	230	90	5
46 50 30 30	T30	5.5	115	230	90	5
46 50 30 40	T40	6.6	115	240	131	5
46 50 30 45	T45	7.8	130	255	136	5

4650L

⊕ TORX® screwdrivers DRALL⁺

for inside TORX® screws, extra long, Chrome Alloy Steel, chrome plated, black tips.




Code	size	mm	L ₁ mm	L ₂ mm	△△ g	📦
46 50 31 15	T15	3.3	250	335	52	5
46 50 31 20	T20	3.8	250	355	64	5
46 50 31 25	T25	4.4	250	355	66	5
46 50 31 30	T30	5.5	250	365	122	5

4656

⊕ TORX® screwdrivers DRALL⁺

with hollow point (TORX® TAMPER RESISTANT), Chrome Alloy Steel, chrome plated, black tips.



Code	size	mm	L ₁ mm	L ₂ mm	△△ g	📦
46 56 30 08	T8	2.3	60	145	35	5
46 56 30 09	T9	2.5	60	145	35	5
46 56 30 10	T10	2.7	80	165	39	5
46 56 30 15	T15	3.3	80	165	39	5
46 56 30 20	T20	3.8	100	205	42	5
46 56 30 25	T25	4.4	100	205	46	5
46 56 30 27	T27	5.0	115	230	90	5
46 56 30 30	T30	5.5	115	230	90	5
46 56 30 40	T40	6.6	115	240	120	5
46 56 30 45	T45	7.8	130	255	118	5

4734

⊕ Cross-head screwdrivers DRALL

Phillips-Recess®, DIN ISO 8764-1, -2, ISO 8764-1, -2, stubby, Chrome Alloy Steel, chrome plated, black tips.



Code	PH size	L ₁ mm	L ₂ mm	△△ g	📦
47 34 10 01	1	25	80	27	10
47 34 10 02	2	25	80	31	10

4744

⊕ Cross-head screwdrivers DRALL

POZIDRIV/SUPADRIV®, DIN ISO 8764-1, -2, ISO 8764-1, -2, stubby, Chrome Alloy Steel, chrome plated, black tips.



Code	PZ size	L ₁ mm	L ₂ mm	△△ g	📦
47 44 10 01	1	25	80	28	10
47 44 10 02	2	25	80	34	10

10507N KK

● Ball ended hexagon drivers DRALL⁺

for use on hexagon socket head screws, swivel angle up to 25° each side, Chrome Alloy Steel, chrome plated, black tips.



Code	mm	L ₁ mm	L ₂ mm	△△ g	📦
73 10 30 03	3	300	385	56	5
73 10 30 05	5	300	415	132	5