

Pipe cutters, Miscellaneous tools

13126-2 LED penlight

Ex

- Ex-rated for zone 1
- Certifications: II 2G Ex e ib IIB T4 Gb, II 2D Ex ib IIIC T60°C IP6X Db.
- Three times brighter than conventional pen torches thanks to powerful LEDs
- Robust, electrically non-conducting, corrosion-proof housing made of ABS/polycarbonate
- High impact resistance and reduced glare thanks to rubber sheathed bezel
- Consistently bright beam throughout 80% of the lifetime of the alkaline batteries due to eLED circuitry
- Rubberised rear pushbutton for continuous or momentary action
- Easy storage due to integrated clip holder close to bezel
- Waterproof to IP 68 down to 3 m depth of water
- Brightness: 35 lumen
- Range: 64 m
- Burn time: 3 hrs.
- Batteries: 2 AAA/LR03, alkaline, 1.5 V (not supplied).



Code	dimensions	g	
77 49 00 12	132 x 24 x 22 mm	32	1

13126-3 LED headlamp

Ex

- Ex-rated for zone 1
- Certifications: SEV 08 ATEX 0163X, II 2G Ex ib IIC T4, II 2D Ex ibD 21 T55°C.
- Waterproof construction for use in all weather conditions
- Three beam modes - white spot, white diffused and red diffused
- High and low power settings
- Large-format ON/OFF button can be easily operated even when wearing heavy gloves
- LED torch module can be removed from housing and used as stand-alone portable working torch
- Beam adjustable using twist knob - no breakable hinges
- With adjustable, elasticated textile strap
- Durable, high-impact construction made of ABS/polycarbonate
- Waterproof to IP 68 down to 10 m depth of water
- Brightness: 65 lumen
- Range: 60 m
- Burn time: 13 hrs.
- Batteries: 3 AAA/LR03, alkaline, 1.5 V (not supplied).



Code	dimensions	g	
77 49 00 13	76 x 38 x 45 mm	81	1

13128 LED torch

- High-end power LED.
- Fast adjustment of light beam thanks to single-handed zoom action.
- Switch with textured profile for 2-stage steady light or flash-light function.
- Designed to facilitate rapid battery change.
- Convenient belt-mounted holder with Velcro fastener.
- Brightness: 320 lumen.
- Range: 260 m.
- Burn time: 50 hrs.
- Batteries: 4 batteries, AAA/LR03, 1.5 V.



Code	dimensions	g	
77 49 00 04	130 x 37 x 37 mm	250	1

13130 Tweezers

straight, blunt,
finely milled inside,
stainless steel.



Code	L mm	g	
77 50 00 01	160	26	5

13131 Tweezers

bent, blunt,
finely milled inside,
stainless steel.



Code	L mm	g	
77 51 00 01	155	21	5

13148 Wire cutter

- for cutting cables, brass, copper, aluminium
- strain-free working thanks to comfy-fit 2-component handle with finger rest
- cutting edges made of stainless steel (INOX HRC 56)
- one wavy/saw edge



Code	L mm	g	
75 27 00 02	150	93	1