

10613 Brake spring pliers

for rivetted brake linings/shoes, Chrome Vanadium, bright nickel-plated.



Code	L mm	g	
76 41 30 01	210	245	6

10613/1 Brake spring pliers

with flexible anvil, for rivetted and glued brake linings/shoes.



Code	L mm	g	
76 41 30 21	330	461	2

12371 Brake calliper file

for removing dust, rust and dirt from brake calliper groove.



Code	L mm	g	
74 54 31 01	260	104	5

12373 Steel wire brush

special slim design.



Code	L mm	Rows	g	
77 44 00 01	230	2	70	10

12900/3 Tyre tread Vernier calliper

- sturdy brass construction
- smooth ground surface



Code	measuring range mm	g	
77 37 10 04	30	42	1

12900/4 Electronic tyre tread Vernier calliper

- large LCD display with clear read-offs, figures 9.5 mm high
- display accuracy 0.01 mm/0.0005"
- ON/OFF push button
- unit of measure switchable mm/inch
- zeroing possible in any position
- incl. 1 x 3 V battery (type CR2032) packed in accordance with UN3091, Class 9



Code	measuring range mm/"	g	
77 37 10 05	25/1	40	1

54-7 INHEX socket

for hexagon socket head screws, size 7 mm, 1/2" O-drive, for changing brake linings.



Code	Type	g	
03 05 00 07	BMW: 518, 520i, 525i, 528i	75	5

1049-9 INHEX socket

for hexagon socket head screws, size 9 mm, 3/8" O-drive, for brake calliper retainers.



Code	Type	g	
02 15 10 09	BMW, MINI	62	5

733/10-11 OPEN-RING insert tool

size 11 mm, use with SERVICE-MANOSKOP® torque wrench No 730/5, for flare nuts on brake lines and bleed screws.



Code	Type	g	
58 23 10 11	Mercedes-Benz	55	1

733/10-12 OPEN-RING insert tool

size 12 mm, for flare nuts on brake pressure regulator, tightening torque 15-18 N-m.



Code	Type	g	
58 23 10 12	BMW	59	1

733/10-14 OPEN-RING insert tool

size 14 mm, for flare nuts on main brake cylinder, tightening torque 16-25 N-m (BMW), for flare nuts on brake lines and bleed screws (Mercedes-Benz).

Code	Type	g	
58 23 10 14	BMW, Mercedes-Benz	60	1

733/10-17 OPEN-RING insert tool

size 17 mm, for flare nuts on main brake cylinder, tightening torque 16-25 N-m.

Code	Type	g	
58 23 10 17	BMW	64	1

733/10-19 OPEN-RING insert tool

size 19 mm, for flare nuts on main brake regulator, tightening torque 30-40 N-m.

Code	Type	g	
58 23 10 19	BMW	80	1