

1068 Air filter claw


for loosening of filter cartridges on air brakes (trucks).



Code	Clamp. width "	total mm	length of claws mm	g	
7462 00 11	1/2	100-145	85	60	925 1

2509 IMPACT sockets

3/4" O-drive, for power drivers, extra deep, with reduced diameter, Chrome Alloy Steel, gunmetal finish.




Code	mm	d ₁ mm	d ₂ mm	L mm	t mm	g	
2509 00 27	27	40.5	44	100	72.5	672	2
2509 00 30	30	44.3	44	100	72.5	728	2
2509 00 32	32	46.8	44	100	72	778	2
2509 00 33	33	48	44	100	72	803	2

for Trilex wheels

2609 IMPACT sockets

1" O-drive, for power drivers, extra deep, with reduced outside diameter, Chrome Alloy Steel, gunmetal finish.



Code	mm	d ₁ mm	d ₂ mm	L mm	t mm	g	
2609 00 27	27	42.3	54	110	80	1001	2
2609 00 30	30	46	54	110	79.5	1047	2
2609 00 32	32	48.5	54	110	79	1015	2
2609 00 33	33	49.8	54	110	78.5	1102	2

for wheel nuts

24-17x19 OPEN-RING spanner

bi-hexagon, size 17 x 19 mm, for all threaded connectors on injector pipes.



Code	Type	g	
4108 17 19	Mercedes-Benz	151	10

51-30 Socket

extra deep, bi-hexagon, size 30 mm, 1/2" O-drive, on injector post.



Code	Type	g	
0302 00 30	Mercedes-Benz	341	5

440-27MB CROW-RING spanner

for setting of electronic injection on 440-HP-engines.



Code	Type	g	
0219 10 27	Mercedes-Benz	92	1

3678 4-pin socket

length 72 mm, 1/2" O-drive, for use on pressure nut of injector post.



Code	Type	g	
0381 00 01	Mercedes-Benz	153	5

1054-10 INHEX socket

for hexagon socket head screws, size 10 mm, length 140 mm, 1/2" O-drive, for cylinder head bolts.



Code	Type	g	
0315 14 10	Mercedes-Benz	150	5

3054X-M12 Screwdriver BIT

for tri-square socket head screws (XZN®), size 12, length 140 mm, Ø 11.5 mm, 1/2" O-drive for cylinder head bolts with tri-square socket head M12.



Code	Type	g	
0326 14 12	Mercedes-Benz	160	5

11068-2 Piston ring compressor

of special spring steel, infinitely variable adjustment, c/w adj. spanner, capacity Ø 90-175 mm.



Code	Type	g	
7414 00 03	Mercedes-Benz	270	1