


12167 VDE VDE extensions 3/8"

Chrome-Alloy-Steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	size	L mm	d mm	⚡ g	
12 42 00 01	3	94	23	84	1
12 42 00 02	6	178	23	162	1
12 42 00 03	10	258	23	224	1

12174 VDE VDE screwdriver sockets 3/8"

for internal TORX® screws; Chrome-Alloy-Steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	size	mm	L mm	d mm	⚡ g	
02 39 00 20	T20	3.8	67	22.8	52	1
02 39 00 25	T25	4.4	67	22.8	52	1
02 39 00 30	T30	5.5	67	22.8	54	1
02 39 00 40	T40	6.6	67	22.8	56	1
02 39 00 45	T45	7.8	67	22.8	58	1

12175 VDE VDE screwdriver sockets 3/8"


for tri-square socket head screws (XZN®); Chrome-Alloy-Steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	size	L mm	d mm	⚡ g	
02 37 00 08	M8	148	22.8	98	1
02 37 00 10	M10	148	22.8	122	1

12177 VDE VDE extensions 1/2"

Chrome-Alloy-Steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	size	L mm	d mm	⚡ g	
13 42 00 01	3	93	27	130	1
13 42 00 02	5	148	27	206	1
13 42 00 03	10	273	27	380	1

12179 VDE VDE sockets 1/2"




HPQ® high performance steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	mm	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	⚡ g	
03 37 00 10	10	19.5	27	9	56	9	22	60	1
03 37 00 11	11	20.8	27	10	56	9.5	22	64	1
03 37 00 12	12	22	27	11	56	13	22	64	1
03 37 00 13	13	23.3	27	12	56	13	22	64	1
03 37 00 14	14	24.9	27.7	13	56	13	20.5	70	1
03 37 00 17	17	29	28.7	15.2	56	15	19.6	82	1
03 37 00 19	19	31.2	30	18	56	16	21.7	98	1
03 37 00 22	22	34.7	31	21	60	16.5	24.9	116	1
03 37 00 24	24	37	31	21	60	18.5	24.9	130	1

12160 VDE VDE single-end open-jaw spanners

Chrome-Alloy-Steel, chrome plated; VDE insulated up to 1000 V; DIN EN 60900; ⚡ AC/1000 V



Code	mm	L mm	b mm	a mm	⚡ g	
44 18 00 10	10	140.7	26	10.5	48	1
44 18 00 13	13	166.4	32.5	11.5	80	1
44 18 00 14	14	181	34.5	11.5	88	1
44 18 00 17	17	200	40	12.5	146	1
44 18 00 19	19	218	44.5	13	184	1
44 18 00 22	22	248	50	13.5	254	1

12160/6 VDE VDE single-end open-jaw spanners

6 pieces;
sizes 10; 13; 14; 17; 19; 22 mm;
Chrome-Alloy-Steel, chrome plated;
in roll-up wallet;
VDE insulated up to 1000 V;
DIN EN 60900;
⚡ AC/1000 V



Code	⚡ g	
96 40 43 01	900	1