

6501 VDE VDE combination pliers

DIN ISO 5746, precision cutting edges for all wires, incl. piano wire, induction hardened cutting edges, approx. 62 HRC, for long life.



6501 7 160



6501 8 160

Code	L mm	Head	Handles	③	④	⑤	⑥	Δg
6501 7 160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	1.8	1.5	10	16	202
6501 7 180	180			2	1.8	12	16	279
6501 7 200	200			2.5	2	13	16	359
6501 8 160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	1.8	1.5	10	16	186
6501 8 180	180			2	1.8	12	16	186
6501 8 200	200			2.5	2	13	16	317

③ Cutting capacity in mm for hard wire

④ Cutting capacity in mm for piano wire

⑤ Cutting capacity in mm for cable

⑥ Cutting capacity in mm² for cable

6507 VDE VDE flat nose pliers, short


DIN ISO 5745, short, flat serrated jaws.



6507 7 160



6507 8 160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	h mm	b mm	Δg
6507 7 160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	30	17	10	5	9	200
6507 8 160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	30	17	10	5	9	181

6508 VDE VDE flat nose pliers, long


DIN ISO 5745, long, flat serrated jaws.



6508 7 160



6508 8 160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	h mm	b mm	Δg
6508 7 160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	50	15	8	3	5	148
6508 8 160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	50	15	8	3	5	166

6523 VDE VDE round nose pliers, short


DIN ISO 5745, for bending wire loops and rings, short, round, ground jaws, fine serrations on gripping areas.



6523 7 160



6523 8 160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	b mm	Δg
6523 7 160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	30	18	10	3	201
6523 8 160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	30	18	10	3	176

6524 VDE VDE round nose pliers, long


DIN ISO 5745, for bending wire loops and rings, long, round, ground jaws, fine serrations on gripping areas.



6524 7 160



6524 8 160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	b mm	Δg
6524 7 160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	47	15.5	8.5	2.5	162
6524 8 160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	47	15.5	8.5	2.5	156