

Socket sets and sockets

6,3
1/4"

DIN
3120


ISO
1174-1

3

44KTXB

⊗ Screwdriver sockets

- with hollow point
- for inside TORX® screws (TORX® TAMPER RESISTANT)
- Chrome Alloy Steel, chrome plated




Code	size	mm	L ₁ mm	L ₂ mm	d mm	△△ g	
0135 1008	T8	2.3	28	16	11.6	10	5
0135 1009	T9	2.5	28	16	11.6	10	5
0135 1010	T10	2.7	28	16	11.6	10	5
0135 1015	T15	3.3	28	16	11.6	10	5
0135 1020	T20	3.8	28	16	11.6	10	5
0135 1025	T25	4.4	28	16	11.6	11	5
0135 1027	T27	5.0	28	16	11.6	10	5
0135 1030	T30	5.5	28	16	11.6	11	5
0135 1040	T40	6.6	28	16	11.6	10	5

44P

⊕ Screwdriver sockets

- for recessed head screws Phillips-Recess®
- tips to DIN 5260
- Chrome Alloy Steel, chrome plated




Code	PH size	L ₁ mm	L ₂ mm	d mm	△△ g	
0129 0001	1	28	16	11.6	12	5
0129 0002	2	28	16	11.6	11	5
0129 0003	3	28	16	11.6	12	5
0129 0004	4	28	16	11.6	14	5

44PZ

⊕ Screwdriver sockets

- for POZIDRIV/SUPADRIV® screws
- Chrome Alloy Steel, chrome plated



Code	PZ size	L ₁ mm	L ₂ mm	d mm	△△ g	
0130 0001	1	28	16	11.6	10	5
0130 0002	2	28	16	11.6	11	5

40CL

Clip strips


- for socket retention
- supplied without sockets



Code	size	L mm	△△ g
8040 0001	1	200	36
8040 0002	2	300	52

Drive tools and accessories

- 1/4" □
- finish: Chrome Alloy Steel, chrome plated



411

Ratchet, fine tooth

- reversible
- 60 teeth
- with 2-component handle
- for use in confined spaces, re-engages after movement of 6°
- DIN 3122/ISO 3315



Code	L mm	b mm	a mm	△△ g	
1123 10 11	118	24	19.5	100	1

415

Ratchet

- reversible
- 22 teeth
- with 2-component handle
- DIN 3122/ISO 3315



Code	L mm	b mm	a mm	△△ g	
1111 10 10	117	22	13	80	5

415QR

QuickRelease ratchet

- reversible
- 22 teeth
- with QuickRelease safety lock
- with 2-component handle
- DIN 3122/ISO 3315
- registered design



Code	L mm	b mm	a mm	△△ g	
1111 00 20	117	22	13	79	1

415QR N

QuickRelease ratchet, fine tooth

- reversible
- 80 teeth
- with QuickRelease safety lock
- with 2-component handle
- for use in confined spaces, re-engages after movement of 4.5°
- construction without screws prevents foreign object damage
- DIN 3122/ISO 3315
- registered design



Code	L mm	b mm	a mm	△△ g	
1111 10 20	117	22.6	10.7	79	1