


50 Sockets



- DIN 3124/ISO 2725-1, E DIN EN 3709, ASME B 107.5 M
- HPQ® high performance steel, chrome plated



Code	mm	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
03010008	8	13	22	7	38	9	22	56	10
03010009	9	13.7	22	8	38	9	22	57	10
03010010	10	14.5	22	9	38	9	22	50	10
03010011	11	15.8	22	10	38	9.5	22	50	10
03010012	12	17	22	11	38	13	22	58	10
03010013	13	18.3	22	12	38	13	22	50	10
03010014	14	19.9	22.7	13	38	13	20.5	60	10
03010015	15	21.2	22.7	14	38	13.5	20.2	62	10
03010016	16	22.4	23.7	15	38	13.5	19.6	63	10
03010017	17	24	23.7	15.2	38	15	19.6	66	10
03010018	18	24.7	23.7	17	38	15.5	19.1	71	10
03010019	19	26.2	25	18	38	16	21.7	78	10
03010020	20	27.2	25	19	42	15	25.5	89	10
03010021	21	28.7	26	20	42	16	25.2	100	10
03010022	22	29.7	26	21	42	16.5	24.9	113	10
03010023	23	30.7	26	20	42	18	25.4	114	5
03010024	24	32	26	21	42	18.5	24.9	117	5
03010025	25	33.2	25	22	42	18.5	24.6	119	5
03010026	26	34.4	25	23	42	18.5	24.3	122	5
03010027	27	36.2	26	24	45	19.5	27	150	5
03010028	28	37.4	27	25	45	19.5	26.7	158	5
03010030	30	39.7	28	27	45	20.5	26.1	171	5
03010031	31	42.2	28	28	47	22	27.9	215	5
03010032	32	42.2	28	29	47	22	27.6	189	5
03010034	34	45	28	31	47	22	27	210	5
03010036	36	48	31	34	52	24	30.9	286	5

50a Sockets




- ASME B 107.1, Fed. Spec. GGG-W-641, SAE AS 954-E (test loads)
- HPQ® high performance steel, chrome plated

Code	"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
03410024	3/8	14.3	22	8.3	38	9	22	51	10
03410028	7/16	16.3	22	9.9	38	9	22	52	10
03410032	1/2	18.3	22	11.5	38	13	22	53	10
03410034	9/16	20.3	22.7	13.1	38	13	20.2	58	10
03410035	19/32	21.3	22.7	13.5	38	13.5	20.1	61	10
03410036	5/8	22.4	23.7	15	38	13.5	19.6	65	10
03410038	11/16	24.2	23.7	16.5	38	15.5	19.2	68	10
03410040	3/4	26.2	25	18	38	16	21.7	78	10
03410041	25/32	27	25	18.6	41	16	24.6	90	5
03410042	13/16	28.2	25	19.4	41	16.5	24.3	95	5
03410044	7/8	29.7	26	21	42	18	24.9	111	5
03410046	15/16	32	26	22.6	42	18.5	24.4	121	5
03410048	1	33.7	27	24.2	42	18.5	24	135	5
03410050	1 1/16	36.2	26	25.8	45	19.5	26.5	155	5
03410052	1 1/8	38.1	28	27.4	45	20	26	167	5
03410054	1 3/16	39	28	28	45	20.5	25.9	178	5
03410056	1 1/4	40	28	30.5	45	21	25.1	196	5
03410058	1 5/16	41.8	28	32.1	47	22	26.7	170	5
03410060	1 3/8	46	28	33.7	50	23	29.2	232	5
03410062	1 7/16	49.4	31	34	54	26	33.1	320	5
03410064	1 1/2	51	31	35	54	26	32.8	325	5

52 Sockets



- DIN 3124/ISO 2725-1, ASME B 107.5M, E DIN EN 3709 (test loads)
- HPQ® high performance steel, chrome plated



Code	mm	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	Δg g	
03030008	8	13	22	7	38	9	22	56	10
03030009	9	13.7	22	8	38	9	22	56	10
03030010	10	14.5	22	9	38	9	22	51	10
03030011	11	15.8	22	10	38	9.5	22	58	10
03030012	12	17	22	11	38	13	22	52	10
03030013	13	18.3	22	12	38	13	22	51	10
03030014	14	19.9	22.7	13	38	13	20.5	59	10
03030015	15	21.2	22.7	14	38	13.5	20.2	60	10
03030016	16	22.4	23.7	15	38	13.5	19.6	65	10
03030017	17	24	23.7	15.2	38	15	19.6	70	10
03030018	18	24.7	23.7	17	38	15.5	19.1	73	10
03030019	19	26.2	25	18	38	16	21.7	80	10
03030020	20	27.2	25	19	42	15	25.5	95	10
03030021	21	28.7	26	20	42	16	25.2	110	10
03030022	22	29.7	26	21	42	16.5	24.9	115	10
03030023	23	30.7	26	20	42	18	25.4	119	5
03030024	24	32	26	21	42	18.5	24.9	125	5
03030025	25	33.2	26	22	42	18.5	24.6	128	5
03030026	26	34.4	25	23	42	18.5	24.3	132	5
03030027	27	36.2	26	24	45	19.5	27	161	5
03030028	28	37.4	27	25	45	19.5	26.7	166	5
03030030	30	39.7	28	27	45	20.5	26.1	186	5
03030032	32	42.2	28	29	47	22	27.6	200	5
03030034	34	45	28	31	47	22	27	235	5
03030036	36	48	31	34	52	24	30.9	305	5

ES 52/17



- 175 x 350 x 47 mm
- 17 pieces

Code	Δg g
968381 12	1760
No	Content
52	1/2" ○ 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

12.5
1/2"

DIN
3120

ISO
1174-1

3