

Socket sets and sockets

12,5
1/2"

DIN
3120

ISO
1174-1

TCS 52/17



- 175 x 350 x 40 mm
- 17 pieces

Code

△
g

96838177

1605

No	Content
52	1/2" Ø 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

TCS 52/18MF



- 175 x 350 x 55 mm
- 18 pieces

Code

△
g

96830359

1850

No	Content
52	1/2" Ø 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32; 34 mm

TCS 50/51/52/32



- 175 x 350 x 50 mm
- 32 pieces

Code

△
g

96838191

2950

No	Content
50	1/2" Ø 8; 9; 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 30 mm
51	1/2" Ø 22; 27 mm
52	1/2" Ø 10; 11; 12; 13; 14; 15; 16; 17; 18; 19; 20; 21; 22; 24; 27; 30; 32 mm

TCS 50a/17



- 175 x 350 x 40 mm
- 17 pieces

Code

△
g

96838780

1685


No	Content
50a	1/2" Ø 3/8; 7/16; 1/2; 9/16; 19/32; 5/8; 11/16; 3/4; 25/32; 13/16; 7/8; 15/16; 1; 1 1/16; 1 1/8; 1 3/16; 1 1/4"

51

○ Sockets



- extra deep
- DIN 3124/ISO 2725-1, E DIN EN 3710, E DIN EN 3709, ASME B 107.5M
- HPQ® high performance steel, chrome plated



Code	Ø mm/"	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	△ g	
03020010 10	10	14.5	22	9	83	19	67	90	10
03020013 13	13	18.3	22	12	83	35	67	122	10
03020014 14	14	19.9	22.7	13	83	35	65.2	129	10
03020015 15	15	21.2	22.7	14	83	35	64.9	125	10
03020016 16	16	22.4	23.7	15	83	35	64.6	145	10
03020216 16-5/8¹⁾	16-5/8	22.4	23.7	15.4	83	19	64.5	137	10
03020017 17	17	24	23.7	16	83	35	64.3	145	10
03020018 18	18	24.7	23.7	17	83	35	64.1	170	10
03020019 19	19	26.2	25	18	83	35	66.7	165	10
03020208 20.8-13/16¹⁾	20.8-13/16	27.7	26	20	83	22	66.2	194	10
03020021 21	21	28.7	26.5	20	83	35	66.2	231	10
03020022 22	22	29.7	27.5	21	83	35	65.5	200	10
03020024 24	24	32	30	21	83	35	66.1	251	5
03020026 26	26	34.4	32.5	23	83	35	65.3	334	5
03020027 27²⁾	27	36.2	34	27	83	20	60	280	5
03020030 30²⁾	30	39.7	37.5	30.2	83	35	65	341	5
03020032 32	32	42.4	40	29	83	35	63.9	435	5

¹⁾ with rubber insert for spark plugs

²⁾ for diesel injector (Audi, Daihatsu, Ford, Mazda, Mercedes, Mitsubishi, Nissan, Opel, Peugeot, Toyota, VW, Volvo)

51a

○ Sockets



- extra deep
- ASME B 107.1, Fed. Spec. GGG-W-641, SAE AS 954-E
- HPQ® high performance steel, chrome plated

Code	Ø "	d ₁ mm	d ₂ mm	d ₃ mm	L mm	t ₁ mm	t ₂ mm	△ g	
03420024 3/8	3/8	14.3	22	8.3	83	19	67	93	5
03420028 7/16	7/16	16.3	22	9.9	83	19	67	102	5
03420032 1/2	1/2	18.3	22	11.5	83	35	67	122	5
03420034 9/16	9/16	20.3	22.7	13.1	83	35	65.2	131	5
03420036 5/8	5/8	22.4	23.7	15	83	35	64.6	135	5
03420038 11/16	11/16	24.2	23.7	16.5	83	35	64.2	158	5
03420040 3/4	3/4	26.2	25	18	83	35	66.7	188	5
03420042 13/16	13/16	27.7	26	19.5	83	35	66.3	170	5
03420044 7/8	7/8	29.7	27.5	21	83	35	65.9	200	5
03420046 15/16	15/16	32	30	22.6	83	35	65.7	281	5
03420048 1	1	33.7	32	24.2	83	35	65	260	5
03420050 1 1/16	1 1/16	36.2	34	25.8	83	35	64.5	359	5
03420052 1 1/8	1 1/8	38.1	36	27.4	83	35	64	300	5
03420054 1 3/16	1 3/16	39	37	28	83	35	63.9	377	5
03420056 1 1/4	1 1/4	40	38	30.5	83	35	63.1	340	5
03420058 1 5/16	1 5/16	41.8	40	32.1	83	35	62.7	375	5
03420060 1 3/8	1 3/8	46	44	33.7	83	35	62.2	506	5
03420062 1 7/16	1 7/16	49.4	47	34	83	35	62.1	635	5
03420064 1 1/2	1 1/2	51	49	35	83	35	61.8	675	5

5100

Rubber insert

- for 20.8 mm (No 46; 51; 51S)

Code	△ g	
09010001	6	5