

5040 Spare parts set for No 504

Content 3 pieces:
1 universal joint, 1 screw,
1 spring washer



Code	Δ g
96 19 08 00	75

for version with chrome plated Philips-head screw

506 Sliding T-handle

• DIN 3122/ISO 3315



Code	L mm	Δ g	
13 07 00 00	300	436	5

506QR QuickRelease sliding T-handle

QR


• with QuickRelease safety lock
• patent



Code	L mm	Δ g	
13 07 10 00	300	470	1

509 Extensions


• DIN 3123/ISO 3316



Code	size	L mm	d mm	Δ g	
13 01 00 01	2	52	23	88	5
13 01 00 04	3	75	23.2	120	5
13 01 00 02	5	130	23.2	191	5
13 01 00 03	10	255	23.2	341	5

509W Wobble-Drive extensions

• swivel angle 15° each side
• maximum torque 200 N·m



Code	size	L mm	d mm	Δ g	
13 01 00 05	2	52	23	80	5
13 01 00 06	3	75	23.2	120	5
13 01 00 07	5	130	23.2	191	5
13 01 00 08	10	255	23.2	341	5

509QR QuickRelease extensions

QR

• patent
• DIN 3123/ISO 3316



Code	size	L mm	d mm	Δ g	
13 01 10 01	2	52	23	90	1
13 01 10 04	3	75	23	123	1
13 01 10 02	5	130	23	187	1
13 01 10 03	10	255	23	341	1

3505 Special extension



Code	L mm	d mm	Δ g	
13 21 00 01	120	23.2	186	1

510 Universal joint

• DIN 3123/ISO 3316




Code	L mm	d mm	Δ g	
13 02 00 00	71	25	146	5

510QR QuickRelease universal joint

QR

• DIN 3123/ISO 3316
• with QuickRelease safety lock
• patent



Code	L mm	d mm	Δ g	
13 02 10 00	80	25	155	1

5513 Set of adaptors

content 5 pieces:

- No 409, 1/4" socket x 3/8" plug
- No 431, 3/8" socket x 1/4" plug
- No 432, 3/8" socket x 1/2" plug
- No 513, 1/2" socket x 3/8" plug
- No 514, 1/2" socket x 3/4" plug



Code	Δ g
96 12 10 03	648

12.5
1/2"

DIN
3120

ISO
1174-1

3