


Screwdrivers

4620

⊖ Screwdrivers for slotted screws DRALL⁺

- DIN ISO 2380-1, -2, DIN 5264, ISO 2380-1, -2
- Chrome Alloy Steel, chrome plated
- black tips



Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
46 20 30 35	1	0.6	3.5	75	160	25	10
46 20 30 40	2	0.8	4.0	100	185	34	10
46 20 30 55	3	1.0	5.5	125	240	79	10
46 20 30 65	4	1.2	6.5	150	265	109	10
46 20 30 80	5	1.6	8.0	175	300	136	10
46 20 31 00	6	1.6	10.0	200	325	163	5
46 20 31 20	7	2.0	12.0	250	375	215	5

4621

⊖ Screwdrivers for slotted screws DRALL⁺

- parallel blades
- as per VSM (Swiss Standard)
- Chrome Alloy Steel, chrome plated
- black tips



Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
46 21 30 25	0	0.4	2.5	80	165	27	10
46 21 30 35	1	0.5	3.5	90	175	26	10
46 21 30 40	2	0.6	4.0	100	185	34	10
46 21 30 55	3	0.8	5.5	120	235	78	10
46 21 30 65	4	1.0	6.5	140	255	96	10
46 21 30 80	5	1.2	8.0	160	275	117	10
46 21 31 00	6	1.6	10.0	180	305	174	10

4622

⊖ Screwdrivers for slotted screws DRALL⁺

- DIN ISO 2380-1, -2, DIN 5264, ISO 2380-1, -2
- with hexagon
- Chrome Alloy Steel, chrome plated
- black tips



Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
46 22 30 55	1	1.0	5.5	100	215	85	10
46 22 30 65	2	1.2	6.5	125	240	100	10
46 22 30 80	3	1.2	8.0	150	275	159	10
46 22 31 00	4	1.6	10.0	175	300	174	10
46 22 31 20	5	2.0	12.0	200	325	240	5
46 22 31 40	6	2.5	14.0	250	375	310	5

4622SK

⊖ Screwdrivers for slotted screws DRALL⁺

- DIN ISO 2380-1, -2, DIN 5264, ISO 2380-1, -2
- with impact cap and hexagonal shank
- Chrome Alloy Steel, chrome plated
- black tips



Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
46 22 32 40	1	0.8	4.0	90	195	50	10
46 22 32 55	2	1.0	5.5	100	215	106	10
46 22 32 65	3	1.2	6.5	125	240	135	5
46 22 32 80	4	1.2	8.0	150	275	191	5
46 22 32 00	5	1.6	10.0	175	300	226	5
46 22 32 20	6	2.0	12.0	200	325	267	5
46 22 33 40	7	2.5	14.0	250	375	340	5

4724

⊖ Carburettor screwdrivers DRALL

- DIN ISO 2380-1, -2, DIN 5264, ISO 2380-1, -2
- stubby
- Chrome Alloy Steel, chrome plated
- black tips




Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
47 24 10 45	1	0.6	3.5	25	80	34	10
47 24 10 60	2	1.0	5.5	25	80	32	10
47 24 10 80	3	1.2	8.0	25	80	39	10

4628

⊖ Electricians screwdrivers for slotted screws DRALL⁺

- DIN ISO 2380-1, -2, DIN 5264, ISO 2380-1, -2
- Chrome Alloy Steel, chrome plated
- black tips



Code	size	a mm	b mm	L ₁ mm	L ₂ mm	Δ g	
46 28 30 25	1	0.4	2.5	60	145	20	10
46 28 30 35	2	0.6	3.5	75	160	40	10
46 28 31 35	3	0.6	3.5	100	185	41	10
46 28 30 40	4	0.8	4.0	125	210	36	10
46 28 30 55	5	1.0	5.5	150	265	92	10
46 28 31 55	6	1.0	5.5	200	315	102	10

4630

⊕ Cross-head screwdrivers DRALL⁺

- Phillips-Recess®
- DIN ISO 8764-1, -2, ISO 8764-1, -2
- Chrome Alloy Steel, chrome plated
- black tips



Code	PH size	L ₁ mm	L ₂ mm	Δ g	
46 30 30 00	0	60	145	20	10
46 30 30 01	1	80	185	35	10
46 30 30 02	2	100	215	90	10
46 30 30 03	3	150	275	146	10