

12965-3R Spare blades 18 mm

- 10 pieces
- for No 12965-3



Code

 Ø Ø
g

7925 1004

75 10

12967
Wire stripping knife with hooked blade


- for cutting round the outer cable insulation and longitudinal cuts
- accurate, fast and safe stripping of all popular round cables from 4-28 mm Ø
- no damage to the inner conductors thanks to infinitely variable adjustment of the cutting depth

Code

 Ø Ø
g

776200 10

82 1

12967R
Spare blade for No 12967


Code

 Ø Ø
g

7925 00 10

2 1

10554
⊖ EURO voltage tester


- built to conform to the new EN standard
- tested to conform to the currently valid VDE GS standard
- with plastic handle
- AC 125-250 V

Code

a

b

L

 Ø Ø
g

7745 0001

1

190

37 10

13000-13003
Hooks and picks

NEW

- universally applicable for punching holes in soft materials, fitting and removing small components such as simmerring seals and O-rings, seals, trim strip clips and panelling



Code

No

L

mm

Model

 Ø Ø
g

7710 1000 13000

155

straight

22

7710 1001 13001

155

45°

22

7710 1002 13002

155

90°

22

7710 1003 13003

155

rounded

24

5

5

13000/4
Set of hooks and picks

NEW

- Content: No 13000 (straight), 13001 (45°), 13002 (90°), 13003 (round)

- universally applicable for punching holes in soft materials, fitting and removing small components such as simmerring seals and O-rings, seals, trim strip clips and panelling
- in textile bag



Code

L

Ø Ø

mm

g

9672 2802

165

144

1

13009
Split-pin puller

NEW



Code

L

Ø Ø

mm

g

7710 10 10

265

138

5

13126-1
LED torch

Ex

- ex-rated for zone 1
- Certifications: SEV 08 ATEX 0164, II 2G Ex e ib IIC T4, II 2D Ex e ibD 21 T98°C
- powerful, extremely durable 2 watt LEDs
- robust, electrically non-conducting, corrosion-proof housing made of ABS/polycarbonate
- high impact resistance and reduced glare thanks to rubber sheathed bezel
- consistently bright beam throughout 80% of the lifetime of the alkaline batteries due to eLED circuitry
- zoom with a twist of the bezel
- rubberised front pushbutton for continuous or momentary action
- waterproof to IP 68 down to 3 m depth of water
- hydrogen scrubber catalyst, polarised battery contacts and 0-psi vent minimize explosive risk from leaking batteries
- battery compartment designed to facilitate rapid battery change
- Brightness: 250 lumen
- Range: 100 m
- Burn time: 5 hrs.
- Batteries: 4 AA/LR06, alkaline, 1.5 V (not supplied)



Code

Dimensions

mm

Ø Ø

g

7749 00 11

170 x 40 x 35

79

1