

## 735/40 Ratchet insert tool

- reversible
- 3/4" ■-drive
- for use with Service-MANOSKOP® torque wrench No 730/40 Quick



| Code               | Typ            | mm           | g   |   |
|--------------------|----------------|--------------|-----|---|
| <b>58 25 00 40</b> | <b>VW/Audi</b> | <b>14x18</b> | 515 | 1 |

## 1421 Bit screwdriver socket

- for inside TORX® screws
- outside ● 1/4" C 6.3 size T45
- length 26 mm
- for use on door hinges
- drive tools: f.e. ratchet reversible No 725/4B and ratchet tap holder No 1820 or ratchet reversible No 725/4B and torque wrench



| Code               | Type                | g |    |
|--------------------|---------------------|---|----|
| <b>08 13 00 45</b> | <b>VW: Golf III</b> | 8 | 10 |

## 1068 Air filter claw


- for loosening of filter cartridges on air brakes (trucks)



| Code               | Clamp. width<br>" | total height<br>mm | length of claws<br>mm | g  |       |
|--------------------|-------------------|--------------------|-----------------------|----|-------|
| <b>74 62 00 11</b> | 1/2               | 100-145            | 85                    | 60 | 925 1 |

## 2509 IMPACT sockets

- 3/4" ○-drive
- for power drivers
- extra deep
- with reduced diameter
- Chrome Alloy Steel, gunmetal finish




| Code               | mm        | d <sub>1</sub><br>mm | d <sub>2</sub><br>mm | L<br>mm | t<br>mm | g   |   |
|--------------------|-----------|----------------------|----------------------|---------|---------|-----|---|
| <b>25 09 00 27</b> | <b>27</b> | 40.5                 | 44                   | 100     | 72.5    | 672 | 2 |
| <b>25 09 00 30</b> | <b>30</b> | 44.3                 | 44                   | 100     | 72.5    | 728 | 2 |
| <b>25 09 00 32</b> | <b>32</b> | 46.8                 | 44                   | 100     | 72      | 778 | 2 |
| <b>25 09 00 33</b> | <b>33</b> | 48                   | 44                   | 100     | 72      | 803 | 2 |

for Trilux wheels

## 2609 IMPACT sockets

- 1" ○-drive
- for power drivers
- extra deep
- with reduced outside diameter
- Chrome Alloy Steel, gunmetal finish



| Code               | mm        | d <sub>1</sub><br>mm | d <sub>2</sub><br>mm | L<br>mm | t<br>mm | g    |   |
|--------------------|-----------|----------------------|----------------------|---------|---------|------|---|
| <b>26 09 00 27</b> | <b>27</b> | 42.3                 | 54                   | 110     | 80      | 1001 | 2 |
| <b>26 09 00 30</b> | <b>30</b> | 46                   | 54                   | 110     | 79.5    | 1047 | 2 |
| <b>26 09 00 32</b> | <b>32</b> | 48.5                 | 54                   | 110     | 79      | 1015 | 2 |
| <b>26 09 00 33</b> | <b>33</b> | 49.8                 | 54                   | 110     | 78.5    | 1102 | 2 |

for wheel nuts

# Special tools for HGVs

## 34c Lkw Wheel brace

- DIN 3119/ISO 6788
- forged centre section, pressed-in extension arms with extra deep forged socket heads
- Chrome Alloy Steel, chrome plated



| Code               | mm/"               | L<br>mm | g    |   |
|--------------------|--------------------|---------|------|---|
| <b>43 03 00 05</b> | 24; 27; 32; ■ 3/4" | 400     | 2058 | 1 |

## 39 Tyre levers

- handy, sturdy construction, purposefully shaped
- Chrome Alloy Steel



| Code               | No              | L<br>mm | g    |   |
|--------------------|-----------------|---------|------|---|
| <b>74 01 06 01</b> | <b>39/1 Lkw</b> | 600     | 897  | 5 |
| <b>74 01 06 02</b> | <b>39/1 Lkw</b> | 600     | 1180 | 5 |
| <b>74 01 06 03</b> | <b>39/1 Lkw</b> | 600     | 900  | 5 |