

## 4670 VDE

### ⊕ VDE cross-head screwdrivers DRALL<sup>+</sup>

- POZIDRIV/SUPADRIV®
- Chrome Alloy Steel
- blade gunmetal finished
- VDE insulated up to 1000 V
- DIN EN 60900
- ⚡ AC/1000 V



| Code              | PZ size  | L <sub>1</sub><br>mm | L <sub>2</sub><br>mm | ⚡<br>g | 📦  |
|-------------------|----------|----------------------|----------------------|--------|----|
| <b>46 70 3000</b> | <b>0</b> | 60                   | 145                  | 36     | 10 |
| <b>46 70 3001</b> | <b>1</b> | 80                   | 185                  | 46     | 10 |
| <b>46 70 3002</b> | <b>2</b> | 100                  | 215                  | 89     | 10 |

## 4675 VDE

### ⊕ VDE TORX® screwdrivers DRALL<sup>+</sup>

- for inside TORX® screws
- Chrome Alloy Steel
- blade gunmetal finished
- VDE insulated up to 1000 V
- DIN EN 60900
- ⚡ AC/1000 V



| code              | size       | mm  | L <sub>1</sub><br>mm | L <sub>2</sub><br>mm | ⚡<br>g | 📦  |
|-------------------|------------|-----|----------------------|----------------------|--------|----|
| <b>46 75 3008</b> | <b>T8</b>  | 2.3 | 60                   | 145                  | 22     | 10 |
| <b>46 75 3010</b> | <b>T10</b> | 2.7 | 60                   | 145                  | 22     | 10 |
| <b>46 75 3015</b> | <b>T15</b> | 3.3 | 75                   | 180                  | 40     | 10 |
| <b>46 75 3020</b> | <b>T20</b> | 3.8 | 100                  | 205                  | 47     | 10 |
| <b>46 75 3025</b> | <b>T25</b> | 4.4 | 100                  | 205                  | 51     | 10 |
| <b>46 75 3030</b> | <b>T30</b> | 5.5 | 100                  | 215                  | 89     | 10 |

## 4695 VDE

### VDE screwdriver set DRALL<sup>+</sup>

Content 6 screwdrivers DRALL<sup>+</sup>:

- VDE insulated up to 1000 V
- DIN EN 60900
- ⚡ AC/1000 V
- ⊖ 4660 VDE:
  - size 1 (0.4 x 2.5 x 75 mm)
  - size 3 (0.6 x 3.5 x 100 mm)
  - size 5 (1.0 x 5.5 x 125 mm)
  - size 6 (1.2 x 6.5 x 150 mm)
- ⊕ 4665 VDE: PH1; PH2



| Code               | ⚡<br>g |
|--------------------|--------|
| <b>96 46 95 15</b> | 595    |

## TCS 4660/4665 VDE



TCS



- 175 x 350 x 40 mm
- 6 pieces

| Code               | ⚡<br>g |
|--------------------|--------|
| <b>96 83 87 66</b> | 391    |

| No              | Content                                                                                                                 |
|-----------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>4660 VDE</b> | size 1 (0.4 x 2.5 x 75 mm)<br>size 3 (0.6 x 3.5 x 100 mm)<br>size 5 (1.0 x 5.5 x 125 mm)<br>size 6 (1.2 x 6.5 x 150 mm) |
| <b>4665 VDE</b> | PH1; PH2                                                                                                                |

## TCS 4665/4670 VDE



TCS



- 175 x 350 x 40 mm
- 7 pieces

| Code               | ⚡<br>g |
|--------------------|--------|
| <b>96 83 87 85</b> | 622    |

| No                                 | Content                             |
|------------------------------------|-------------------------------------|
| <b>4665 VDE</b><br><b>4670 VDE</b> | PH0; PH1; PH2; PH3<br>PZ0; PZ1; PZ2 |

## TCS 4675 VDE



TCS



- 175 x 350 x 40 mm
- 6 pieces

| Code               | ⚡<br>g |
|--------------------|--------|
| <b>96 83 87 93</b> | 385    |

| No              | Content                           |
|-----------------|-----------------------------------|
| <b>4675 VDE</b> | sizes T8; T10; T15; T20; T25; T30 |

## 4798 VDE

### VDE set of interchangeable screwdrivers

- 14 pieces
- two-component handle with soft-grip zones for use as precision tools
- attachable rotating cap for interchangeable blades
- automatic locking system prevents inadvertent extraction
- VDE insulated up to 1000 V
- DIN EN 60900
- ⚡ AC/1000 V
- Content:
  - 1x two-component handle
  - 1x attachable rotating cap
  - ⊖ 2.5 x 0.4; 3.0 x 0.5; 3.5 x 0.6; 4.0 x 0.8; 5.5 x 1.0; 6.5 x 1.2 mm
  - ⊕ PH1; PH2
  - ⊕ PZ2
  - ⊕ T10; T15; T20



| Code               | ⚡<br>g |
|--------------------|--------|
| <b>96 46 95 11</b> | 814    |