

6523 VDE VDE round nose pliers, short


- DIN ISO 5745
- for bending wire loops and rings
- short, round, ground jaws
- fine serrations on gripping areas



65237160



65238160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	b mm	Δg g
65237160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	30	18	10	3	201
65238160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	30	18	10	3	176

6524 VDE VDE round nose pliers, long


- DIN ISO 5745
- for bending wire loops and rings
- long, round, ground jaws
- fine serrations on gripping areas



65247160



65248160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	b mm	Δg g
65247160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	47	15.5	8.5	2.5	162
65248160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	47	15.5	8.5	2.5	156

6529 VDE VDE snipe nose pliers with cutter (radio- or telephone pliers)


- DIN ISO 5745
- Form A (straight)
- half round, long tapering, serrated jaws, with burner hole
- precision cutting edges for soft and hard wires
- induction hardened cutting edges, approx. 60 HRC



65297160



65298160



Code	L mm	Head	Handles	L ₃ mm	W mm	T mm	h mm	b mm	Δg g
65297160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	51	16	9	3	2.5	174
65297200	200			73	17	9	3	2.5	226
65298160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	51	16	9	3	2.5	158
65298200	200			73	17	9	3	2.5	202

6530 VDE VDE snipe nose pliers with cutter (radio- or telephone pliers)


- DIN ISO 5745
- Form B, bent 45°
- half round, long tapering, serrated jaws, with burner hole
- precision cutting edges for soft and hard wires
- induction hardened cutting edges, approx. 60 HRC



65307160



65308160



Code	L mm	Head	Handles	L ₂ mm	L ₃ mm	W mm	T mm	h mm	b mm	Δg g
65307160	160	chrome plated	dip-coated insulation DIN EN 60900, $\triangle$ AC/1000 V	24	55	16	9	3	2.5	185
65307200	200			28	76	17	9	3.5	2.5	230
65308160	160	chrome plated	insulated, with plastic sleeves, DIN EN 60900, $\triangle$ AC/1000 V	24	55	16	9	3	2.5	154
65308200	200			28	76	17	9	3.5	3	201